



KBP200 THRU KBP210


SINGLE PHASE 2.0 AMPS . SILICON BRIDGE RECTIFIERS



VOLTAGE RANGE
50 to 1000 Volts
CURRENT
2.0 Amperes

FEATURES

- * Ideal for printed circuit board
- * High Surge Current Capability
- * Reliable low cost construction
- * Small size, simple installation



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating. at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%

TYPE NUMBER	SYMBOLS	KBP 200	KBP 201	KBP 202	KBP 204	KBP 206	KBP 208	KBP 210	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Bridge Input Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum D. C Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current @ $T_A = 50^\circ C$	$I_{F(AV)}$	2.0							A
Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	50							A
Maximum Forward Voltage Drop per element @ 1.0A (Note)	V_F	1.10							V
Maximum Reverse Current at Rated @ $T_A = 25^\circ C$ D. C. Blocking Voltage per element @ $T_A = 100^\circ C$	I_R	10 500							μA μA
Operating Temperature Range	T_J	- 55 to + 125							$^\circ C$
Storage Temperature Range	T_{STG}	- 55 to + 150							$^\circ C$

NOTE: Mounted on glass - epoxy P. C. B, Soldering land $\phi 3mm$.

RATINGS AND CHARACTERISTIC CURVES (KBP200 THRU KBP210)

FIG. 1-MAXIMUM NON - REPETITIVE PEAK FORWARD SURGE CURRENT - PER ELEMENT




FIG. 2-TYPICAL FORWARD OUTPUT CURRENT DERATING CURVE




FIG. 3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS - PER ELEMENT




FIG. 4-TYPICAL REVERSE CHARACTERISTICS PER ELEMENT

