

# LINEAR SYSTEMS

## *Linear Integrated Systems*

### FEATURES

DIRECT REPLACEMENT FOR SILICONIX J/SST201 SERIES

LOW CUTOFF VOLTAGE	$V_{GS(off)} \leq 1.5V$
--------------------	-------------------------

HIGH GAIN	$A_v = 80 V/V$
-----------	----------------

### ABSOLUTE MAXIMUM RATINGS<sup>1</sup>

@ 25 °C (unless otherwise stated)

#### Maximum Temperatures

Storage Temperature	-65 to +150 °C
---------------------	----------------

Operating Junction Temperature	-55 to +135 °C
--------------------------------	----------------

#### Maximum Power Dissipation

Continuous Power Dissipation	350mW
------------------------------	-------

#### Maximum Current

Forward Gate Current	50mA
----------------------	------


#### Maximum Voltages

Gate to Drain Voltage	-40V
-----------------------	------

Gate to Source Voltage	-40V
------------------------	------

# J/SST201 SERIES


## HIGH GAIN N-CHANNEL JFET



### ELECTRICAL CHARACTERISTICS @ 25 °C (unless otherwise stated)


SYMBOL	CHARACTERISTIC	MIN	TYP	MAX	UNITS	CONDITIONS
BV <sub>GSS</sub>	Gate to Source Breakdown Voltage	J/SST201, 202	-40		V	I <sub>G</sub> = -1µA, V <sub>DS</sub> = 0V
		J/SST204	-25			
V <sub>GS(off)</sub>	Gate to Source Cutoff Voltage	J/SST201	-0.3	-1.5	V	V <sub>DS</sub> = 15V, I <sub>D</sub> = 10nA
		J/SST202	-0.8	-4		
		J/SST204	-0.3	2		
I <sub>DSS</sub>	Drain to Source Saturation Current <sup>2</sup>	J/SST201	0.2	1	mA	V <sub>DS</sub> = 15V, V <sub>GS</sub> = 0V
		J/SST202	0.9	4.5		
		J/SST204	0.2	3		
I <sub>GSS</sub>	Gate Reverse Current	-2		-100	pA	V <sub>GS</sub> = -20V, V <sub>DS</sub> = 0V
I <sub>G</sub>	Gate Operating Current		-2			V <sub>DG</sub> = 10V, I <sub>D</sub> = 0.1mA
I <sub>D(off)</sub>	Drain Cutoff Current		2			V <sub>DS</sub> = 15V, V <sub>GS</sub> = -5V
g <sub>fs</sub>	Forward Transconductance	J/SST201, 204	0.5		mS	V <sub>DS</sub> = 15V, V <sub>GS</sub> = 0V, f = 1kHz
		J/SST202	1			
C <sub>iss</sub>	Input Capacitance		4.5		pF	V <sub>DS</sub> = 15V, V <sub>GS</sub> = 0V, f = 1MHz
C <sub>rss</sub>	Reverse Transfer Capacitance		1.3			
e <sub>n</sub>	Noise Voltage		6		nV/√Hz	V <sub>DS</sub> = 10V, V <sub>GS</sub> = 0V, f = 1kHz

## TO-92



DIMENSIONS  
IN INCHES.

## SOT-23



DIMENSIONS IN  
MILLIMETERS

1. Absolute maximum ratings are limiting values above which serviceability may be impaired.
2. Pulse Test: PW ≤ 300µs, Duty Cycle ≤ 3%

Information furnished by Linear Integrated Systems is believed to be accurate and reliable. However, no responsibility is assumed for its use; nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Linear Integrated Systems.