


**BRIGHT RED MSQ6111C, MSQ6141C
GREEN MSQ6411C, MSQ6441C
HIGH EFF. RED MSQ6911C, MSQ6941C**

PACKAGE DIMENSIONS



FEATURES

- Easy to read digit
- Common anode or cathode
- Low power consumption
- Highly visible bold segments
- High brightness with high contrast
- White segments on a grey face for MSQ64X1C and MSQ61X1C.
- Red segments and red face for MSQ69X1C
- Directly compatible with integrated circuits
- Rugged plastic/epoxy construction

APPLICATIONS

- Digital readout displays
- Instrument panels

NOTES: Dimensions are in mm (inch).
All pins are 0.5 (0.02) diameter
Tolerances are ± 0.25 (0.1) unless otherwise noted.

MODEL NUMBERS

<u>Part number</u>	<u>Color</u>	<u>Description</u>
MSQ6111C	Bright Red	Common Anode; right hand decimal
MSQ6141C	Bright Red	Common Cathode; right hand decimal
MSQ6411C	Green	Common Anode; right hand decimal
MSQ6441C	Green	Common Cathode; right hand decimal
MSQ6911C	High Efficiency Red	Common Anode; right hand decimal
MSQ6941C	High Efficiency Red	Common Cathode; right hand decimal

(For other color options, contact your local area Sales Office)

ABSOLUTE MAXIMUM RATING (T_A=25°C unless otherwise specified)


	B.Red MSQ 6111C 6141C	Green MSQ 6411C 6441C	High Eff. Red MSQ 6911C 6941C	Unit
Part number				
Continuous forward current (I _f) Per Segment	15	30	30	mA
Peak forward current per die (I _f) (at f = 10.0 KHz, Duty factor = 1/10)	60	90	90	mA
Power dissipation (P _D)	40*	70*	70*	mW
*Derate Linearly from 25°C	0.17	0.33	0.33	mW/°C
Reverse voltage per dice.....				5V
Operating and Storage temperature range.....				- 25°C to +85°C
Lead soldering time (at 1/16 inch from the bottom of lamp).....				5 seconds @ 230°C

ELECTRO - OPTICAL CHARACTERISTICS (T_A = 25°C unless otherwise specified)


	Bright Red MSQ 6111C 6141C	Green MSQ 6411C 6441C	High Eff. Red MSQ 6911C 6941C	Test Condition
<u>Part number</u>				
Luminous intensity (ucd)				
minimum	300	800	900	I _f = 20mA
typical	700	2200	2200	I _f = 20mA
Forward voltage (V _f)				
typical	2.1	2.1	2.0	I _f = 20mA
maximum	2.6	2.8	2.8	
Peak wavelength (nm)	697	570	635	I _f = 20mA
Spectral line half width (nm)	90	30	45	I _f = 20mA
Reverse breakdown voltage (V _R)	5	5	5	I _r = 100uA

PINOUT

MSQ6X11C - Common Anode



MSQ6X41C - Common Cathode



GRAPHICAL DATA - Bright Red ($T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig.1 FORWARD CURRENT VS. FORWARD VOLTAGE.




Fig.2 SPECTRAL RESPONSE




Fig.3 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




Fig.5 LUMINOUS INTENSITY VS. DUTY CYCLE




Fig.4 MAXIMUM ALLOWABLE DC CURRENT PER SEGMENT VS. A FUNCTION OF AMBIENT TEMPERATURE.




Fig.6 MAX PEAK CURRENT VS. DUTY CYCLE % (REFRESH RATE f = 1 KHz)

GRAPHICAL DATA - Green ($T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig.1 FORWARD CURRENT VS. FORWARD VOLTAGE.




Fig.2 SPECTRAL RESPONSE




Fig.3 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




Fig.5 LUMINOUS INTENSITY VS. DUTY CYCLE




Fig.4 MAXIMUM ALLOWABLE DC CURRENT PER SEGMENT CS. A FUNCTION OF AMBIENT TEMPERATURE.




Fig. 6 MAX PEAK CURRENT VS. DUTY CYCLE % (REFRESH RATE $f=1\text{ KHz}$)

GRAPHICAL DATA - High Efficiency Red ($T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig.1 FORWARD CURRENT VS. FORWARD VOLTAGE.




Fig.2 SPECTRAL RESPONSE




Fig.3 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




Fig.5 LUMINOUS INTENSITY VS. DUTY CYCLE




Fig.4 MAXIMUM ALLOWABLE DC CURRENT PER SEGMENT VS. A FUNCTION OF AMBIENT TEMPERATURE.




Fig. 6 MAX PEAK CURRENT VS. DUTY CYCLE % (REFRESH RATE $f = 1\text{ KHz}$)



FAIRCHILD

SEMICONDUCTOR™

**0.56 INCH (14.2 MM)
FOUR DIGIT STICK DISPLAY**

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.