



Technical Data Sheet

3.0mm Multi-Color Round Type LED Lamps

209HGW

■ Features :

- Two chips are matched for uniform light output, wide viewing angle
- Long life-solid state reliability
- I.C. compatible/Low power consumption
- Pb free



■ Descriptions :

- The 209 LED lamps contain two integral chips and is available as both bicolor and bipolar types.
- The Bright Red and Green light is emitted by diodes of GaP and GaP respectively.
- Type of bipolar lamps are both White Diffused and Color Diffused while the bicolor are White Diffused.

■ Applications :

- TV set
- Monitor
- Telephone
- Computer

PART NO.	Chip		Lens Color
	Material	Emitted Color	
209HGW	GaP	Bright Red	White Diffused
	GaP	Green	




Technical Data Sheet

3.0mm Multi-Color Round Type LED Lamps

209HGW

Package Dimensions



Notes: 1. All dimensions are in millimetres

2. An epoxy meniscus may extend about 1.5mm(0.059") down to the lead.
3. Tolerances unless Dimension ± 0.25 mm.

Absolute Maximum Ratings at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Rating	Unit
Forward Current	I _F	H 15	mA
		G 30	
Operating Temperature	T _{opr}	-40 to +85	°C
Storage Temperature	T _{stg}	-40 to +100	°C
Soldering Temperature	T _{sol}	260 ± 5	°C
Power Dissipation	P _d	H 45	mW
		G 100	
Peak Forward Current	I _F (Peak)	H 50	mA
		G 160	
Reverse Voltage	V _R	5	V

Note: *1: I_{FP} Conditions -- Pulse Width \leq 1msec and Duty \leq 1/10.

*2: Soldering time \leq 5 seconds.



Technical Data Sheet

3.0mm Multi-Color Round Type LED Lamps

209HGW

Electro-Optical Characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	I _v H	0.4	0.8	/	mcd	I _F = 10 mA
	G	1.0	2.0	/		I _F = 20 mA
Viewing Angle	2θ 1/2	/	70	/	deg	I _F = 20 mA
Peak Wavelength	λ _p H	/	697	/	nm	I _F = 10 mA
	G	/	565	/		I _F = 20 mA
Dominant Wavelength	λ _d H	/	650	/	nm	I _F = 10 mA
	G	/	570	/		I _F = 20 mA
Spectrum Radiation Bandwidth	Δλ H	/	90	/	nm	I _F = 10 mA
	G	/	30	/		I _F = 20 mA
Forward Voltage	V _F H	1.5	2.0	2.4	V	I _F = 10 mA
	G	1.7	2.1	2.4		I _F = 20 mA
Reverse Current	I _R	/	/	10	μ A	V _R = 5 V









Technical Data Sheet

3.0mm Multi-Color Round Type LED Lamps

209HGW

Typical Electro-Optical Characteristic Curves:

(H)











Technical Data Sheet

3.0mm Multi-Color Round Type LED Lamps

209HGW

Typical Electro-Optical Characteristic Curves:

(G)





Technical Data Sheet

3.0mm Multi-Color Round Type LED Lamps

209HGW

■ Reliability test items and conditions:

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	10 SEC	76 PCS	0/1
2	Temperature Cycle	H : +100°C 15min ∫ 5 min L : -40°C 15min	300 CYCLES	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min ∫ 10 sec L : -10°C 5min	300 CYCLES	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -40°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	TEMP : 25°C H: IF = 10mA ; G: IF=20mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C / 85% RH	1000 HRS	76 PCS	0/1



Technical Data Sheet

3.0mm Multi-Color Round Type LED Lamps

209HGW

Packing Quantity Specification

1.500PCS/1Bag , 6Bags/1Box

2.10Boxes/1Carton

Label Form Specification

EVERLIGHT

CPN:

P/N:



209HGW

QTY:



CAT:

HUE:

REF:

LOT NO: EL



MADE IN TAIWAN

CPN: Customer's Production Number

P/N : Production Number

QTY: Packing Quantity

CAT: Ranks

HUE: Peak Wavelength

REF: Reference

LOT No: Lot Number

MADE IN TAIWAN: Production Place

Notes

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
3. These specification sheets include materials protected under copyright of EVERLIGHT corporation. Please don't reproduce or cause anyone to reproduce them without EVERLIGHT's consent.

EVERLIGHT ELECTRONICS CO., LTD.

Office: No 25, Lane 76, Sec 3, Chung Yang Rd,

Tucheng Tainei 236 Taiwan R O C

Tel: 886-2-2267-2000, 2267-9936

Fax: 886-2267-6244, 2267-6189, 2267-6306

<http://www.everlight.com>

This datasheet has been downloaded from:

www.DatasheetCatalog.com

Datasheets for electronic components.