

**IS1, IS5, IS74
ISD1, ISD5, ISD74
ISQ1, ISQ5, ISQ74**



HIGH DENSITY PHOTOTRANSISTOR OPTICALLY COUPLED ISOLATORS

APPROVALS

- UL recognised, File No. E91231
- 'X' SPECIFICATION APPROVALS
 - VDE 0884 in 3 available lead form :-
 - STD
 - G form
 - SMD approved to CECC 0080
 - IS1X, IS5X, IS74X are certified to EN60950 by the following Test Bodies :-
 - Nemko - Certificate No. P01102464
 - Fimko - Certificate No. FI18166
 - Semko - Reference No. 0202037/01-22
 - Demko - Certificate No. 311158-01
 - BSI approved - Certificate No. 8001

DESCRIPTION



The IS*, ISD*, ISQ* series of optically coupled isolators consist of infrared light emitting diodes and NPN silicon photo transistors in space efficient dual in line plastic packages.

FEATURES

- Options :-
 - 10mm lead spread - add G after part no.
 - Surface mount - add SM after part no.
 - Tape&reel - add SMT&R after part no.
- High Isolation Voltage (5.3kV_{RMS}, 7.5kV_{PK})
- High BV_{CEO} (70V min) IS5, ISD5, ISQ5

APPLICATIONS

- Computer terminals
- Industrial systems controllers
- Signal transmission between systems of different potentials and impedances



ISOCOM COMPONENTS LTD

Unit 25B, Park View Road West,
Park View Industrial Estate, Brenda Road
Hartlepool, Cleveland, TS25 1YD
Tel: (01429) 863609 Fax :(01429) 863581

ABSOLUTE MAXIMUM RATINGS
(25°C unless otherwise specified)

Storage Temperature	-40°C to +125°C
Operating Temperature	-25°C to +100°C
Lead Soldering Temperature (1/16 inch (1.6mm) from case for 10 secs)	260°C

INPUT DIODE

Forward Current	50mA
Reverse Voltage	6V
Power Dissipation	70mW

OUTPUT TRANSISTOR

Collector-emitter Voltage BV _{CEO} IS5, ISD5, ISQ5	70V
IS1, ISD1, ISQ1, IS74, ISD74, ISQ74	50V
Emitter-collector Voltage BV _{ECO}	6V
Power Dissipation	150mW

POWER DISSIPATION

Total Power Dissipation	170mW
(derate linearly 2.67mW/°C above 25°C)	


ELECTRICAL CHARACTERISTICS (T_A = 25°C Unless otherwise noted)

PARAMETER		MIN	TYP	MAX	UNITS	TEST CONDITION
Input	Forward Voltage (V _F)		1.2	1.65	V	I _F = 50mA
	Reverse Current (I _R)			10	µA	V _R = 4V
Output	Collector-emitter Breakdown (BV _{CEO}) IS5, ISD5, ISQ5	70			V	I _C = 1mA
	IS1, ISD1, ISQ1, IS74, ISD74, ISQ74	50			V	(Note 2)
	Emitter-collector Breakdown (BV _{ECO})	6			V	I _E = 100µA
	Collector-emitter Dark Current (I _{CEO})			50	nA	V _{CE} = 10V
Coupled	Current Transfer Ratio (CTR) (Note 2) IS1, ISD1, ISQ1	20		300	%	10mA I _F , 10V V _{CE}
	IS5, ISD5, ISQ5	50		400	%	10mA I _F , 10V V _{CE}
	IS74, ISD74, ISQ74	12.5			%	16mA I _F , 5V V _{CE}
	Saturated Current Transfer Ratio IS1, ISD1, ISQ1		75		%	10mA I _F , 0.4V V _{CE}
	IS5, ISD5, ISQ5		100		%	10mA I _F , 0.4V V _{CE}
	IS74, ISD74, ISQ74	12.5			%	16mA I _F , 0.5V V _{CE}
	Input to Output Isolation Voltage V _{ISO}	5300			V _{RMS}	See note 1
	Input to Output Isolation Voltage V _{ISO}	7500			V _{PK}	See note 1
	Input-output Isolation Resistance R _{ISO}	5x10 ¹⁰			Ω	V _{IO} = 500V (note 1)
	Output Rise Time tr			2.6	µs	I _F = 5mA
	Output Fall Time tf			2.2	µs	V _{CC} = 5V, R _L = 75Ω


Note 1 Measured with input leads shorted together and output leads shorted together.

Note 2 Special Selections are available on request. Please consult the factory.


Collector Power Dissipation vs. Ambient Temperature




Relative Current Transfer Ratio vs. Ambient Temperature




Forward Current vs. Ambient Temperature



Relative Current Transfer Ratio vs. Forward Current



Relative Current Transfer Ratio vs. Ambient Temperature



Relative Current Transfer Ratio vs. Forward Current

