


NPN SILICON PLANAR MEDIUM POWER TRANSISTOR

2N6731

ISSUE 1 – MARCH 94

FEATURES

- * 80 Volt V_{CEO}
- * Gain of 100 at $I_C = 350$ mA
- * $P_{tot}=1$ Watt



ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V_{CBO}	100	V
Collector-Emitter Voltage	V_{CEO}	80	V
Emitter-Base Voltage	V_{EBO}	5	V
Peak Pulse Current	I_{CM}	2	A
Continuous Collector Current	I_C	1	A
Power Dissipation at $T_{amb} = 25^\circ\text{C}$	P_{tot}	1	W
Operating and Storage Temperature Range	$T_j:T_{stg}$	-55 to +200	°C

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ\text{C}$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	100			V	$I_C=100\mu\text{A}, I_E=0$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	80			V	$I_C=10\text{mA}, I_B=0^*$
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	5			V	$I_E=1\text{mA}, I_C=0$
Collector Cut-Off Current	I_{CBO}			0.1	μA	$V_{CB}=80\text{V}, I_E=0$
Emitter Cut-Off Current	I_{EBO}			10	μA	$V_{EB}=5\text{V}, I_C=0$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$			0.35	V	$I_C=350\text{mA}, I_B=35\text{mA}^*$
Base-Emitter Turn-On Voltage	$V_{BE(on)}$			1.0	V	$I_C=350\text{mA}, V_{CE}=2\text{V}^*$
Static Forward Current Transfer Ratio	h_{FE}	100 100		300		$I_C=10\text{mA}, V_{CE}=2\text{V}^*$ $I_C=350\text{mA}, V_{CE}=2\text{V}^*$
Transition Frequency	f_T	50		500	MHz	$I_C=200\text{mA}, V_{CE}=5\text{V}$ $f=20\text{MHz}$
Collector-Base Capacitance	C_{CB}			20	pF	$V_{CB}=10\text{V}, f=1\text{MHz}$

*Measured under pulsed conditions. Pulse width=300μs. Duty cycle ≤2%