





## SPECIFICATIONS

### PHYSICAL CHARACTERISTICS for single plate:

DIAMETER .....	33 mm
ACTIVE DIAMETER .....	25 mm
THICKNESS .....	0.317 mm
FLATNESS .....	<±.015mm
PORE SIZE .....	5 μm
CENTER-TO-CENTER SPACING .....	5.8 μm
BIAS ANGLE .....	12°
L/D RATIO .....	56:1
OPEN AREA RATIO .....	58%

### ELECTRICAL CHARACTERISTICS for matched set:

GAIN @ 2400 VOLTS .....	8 x 10 <sup>7</sup>
RESISTANCE .....	75 MΩ
PULSE WIDTH .....	1 ns, depending upon ..... detector impedance
MAXIMUM COUNT RATE .....	10 MHz
DARK COUNT RATE .....	*5 counts/sec./cm <sup>2</sup> @ 2.0kV
PULSE HEIGHT RATIO .....	70-100%

*\* measurement based on a chevron pair*

Export of this product is regulated by the U.S. Dept. of State in accordance with guidelines of "International Traffic in Arms Regulations (ITAR)" per Title 22, Code of Federal Regulations, Parts 120-130. Approved for Unlimited Public Release per 02-S-0323

#### Form 519B-0203

© 2003 K and M Electronics, Inc., a Subsidiary of ITT Industries, Inc. All rights reserved. Specifications subject to change without notice and are believed to be reliable; however, should not be construed as a warranty of performance and no express or implied warranty is made with respect to same.

**K and M Electronics**



11 Interstate Drive  
West Springfield, MA 01089-4531 USA  
(413) 263-6200 • 800-442-4334 • fax: (413) 737-0608  
<http://www.kandm.com>