



## ST2600C..R SERIES

### PHASE CONTROL THYRISTORS

### Hockey Puk Version

#### Features

- Double side cooling
- High surge capability
- High mean current
- Fatigue free

#### Typical Applications

- DC motor controls
- Controlled DC power supplies
- AC controllers

#### Major Ratings and Characteristics

Parameters	ST2600C..R	Units
$I_{T(AV)}$	2220	A
@ $T_C$	80	°C
$I_{T(AV)}$	2630	A
@ $T_{hs}$	55	°C
$I_{T(RMS)}$	4800	A
@ $T_{hs}$	25	°C
$I_{TSM}$	46000	A
@ 60Hz	48200	A
$I^2t$	10580	KA <sup>2</sup> s
@ 60Hz	9640	KA <sup>2</sup> s
$V_{DRM}/V_{RRM}$	2000 to 3000	V
$t_q$ typical	400	μs
$T_J$ max.	125	°C

2630A

(R-PUK)



## ST2600C..R Series

### ELECTRICAL SPECIFICATIONS

#### Voltage Ratings

Type number	Voltage Code	$V_{DRM}/V_{RRM}$ , max. repetitive peak and off-state voltage V	$V_{RSM}$ , maximum non-repetitive peak voltage V	$I_{DRM}/I_{RRM}$ max. @ $T_c = 125^\circ C$ mA
ST2600C..R	20	2000	2100	250
	22	2200	2300	
	24	2400	2500	
	26	2600	2700	
	28	2800	2900	
	30	3000	3100	

#### On-state Conduction

Parameter	ST2600C..R	Units	Conditions						
$I_{T(AV)}$ Max. average on-state current @ Case temperature	2220 (1440)	A	180° conduction, half sine wave double side (single side [anode side]) cooled						
	80	°C							
$I_{T(AV)}$ Max. average on-state current @ Heatsink temperature	2630 (1160)	A	DC @ 25°C heatsink temperature double side cooled	A	t = 10ms t = 8.3ms t = 10ms t = 8.3ms	No voltage reapplied 50% $V_{RRM}$ reapplied No voltage reapplied 50% $V_{RRM}$ reapplied			
	55 (85)	°C							
$I_{T(RMS)}$ Max. RMS on-state current	4800	A							
$I_{TSM}$ Max. peak, one-cycle non-repetitive surge current	46000	A	Sinusoidal half wave, Initial $T_c = 125^\circ C$	KA <sup>2</sup> s	t = 10ms t = 8.3ms t = 10ms t = 8.3ms	No voltage reapplied 50% $V_{RRM}$ reapplied No voltage reapplied 50% $V_{RRM}$ reapplied			
	48200								
	36800								
	38500								
$I^2t$ Maximum $I^2t$ for fusing	10580	KA <sup>2</sup> s	Initial $T_c = 125^\circ C$	t = 10ms t = 8.3ms t = 10ms t = 8.3ms	No voltage reapplied 50% $V_{RRM}$ reapplied				
	9640								
	6770								
	6150								
$V_{T(TO)}$ Max. value of threshold voltage	0.89	V	$T_j = T_{j\max}$						
$r_t$ Max. value of on-state slope resistance	0.19	mΩ	$T_j = T_{j\max}$						
$V_{TM}$ Max. on-state voltage	1.45	V	$I_{pk} = 2900A, T_c = 25^\circ C$						
$I_L$ Max. (typical) latching current	300 (100)	mA	$T_j = 25^\circ C, V_D = 5V$						

#### Switching

Parameter	ST2600C..R	Units	Conditions	
$di/dt$ Max. repetitive 50Hz (no repetitive) rate of rise of turned-on current	150 (300)	A/μs	From 67% $V_{DRM}$ gate drive 20V, 20Ω, $t_r = 1\mu s$ $T_j = T_{j\max}$	
$t_d$ Maximum delay time	2.0	μs	Gate drive 30V, 15Ω, $V_d = 67\% V_{DRM}, T_j = 25^\circ C$ Rise time 0.5μs	
$t_q$ Typical turn-off time	400		$I_T = 800A, t_p = 1ms, T_j = T_{j\max}, V_{RM} = 50V,$ $dI_{RR}/dt = 20A/\mu s, V_{DR} = 67\% V_{DRM}, dV/dt = 20V/\mu s$ linear	

ST2600C..R Series




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - On-state Power Loss Characteristics




Fig. 4 - On-state Voltage Drop Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current

## ST2600C..R Series

---




Fig. 7 - Stored Charged




Fig. 8 - Thermal Impedance  $Z_{thJ-C}$  Characteristics




Fig. 9 - Gate Characteristics

## ST2600C..R Series

### Blocking

Parameter	ST2600C..R	Units	Conditions
dv/dt Maximum linear rate of rise of off-state voltage	500	V/μs	$T_J = T_{J\max}$ to 67% rated $V_{DRM}$
$I_{RRM}$ $I_{DRM}$ Max. peak reverse and off-state leakage current	250	mA	$T_J = 125^\circ C$ rated $V_{DRM}/V_{RRM}$ applied

### Triggering

Parameter	ST2600C..R	Units	Conditions
$P_{GM}$ Maximum peak gate power	150	W	$t_p = 100\mu s$
$P_{G(AV)}$ Maximum average gate power	10		
$I_{GM}$ Max. peak positive gate current	30	A	Anode positive with respect to cathode
$V_{GM}$ Max. peak positive gate voltage	30	V	Anode positive with respect to cathode
$-V_{GM}$ Max. peak negative gate voltage	0.25	V	Anode negative with respect to cathode
$I_{GT}$ Maximum DC gate current required to trigger	400	mA	$T_C = 25^\circ C, V_{DRM} = 5V$
$V_{GT}$ Maximum gate voltage required to trigger	4	V	$T_C = 25^\circ C, V_{DRM} = 5V$
$V_{GD}$ DC gate voltage not to trigger	0.25	V	$T_C = 125^\circ C$ Max. gate current/voltage not to trigger is the max. value which will not trigger any unit with rated $V_{DRM}$ anode-to-cathode applied

### Thermal and Mechanical Specification

Parameter	ST2600C..R	Units	Conditions
$T_J\max$ . Max. operating temperature	125	°C	On-state (conducting)
$T_{stg}$ Max. storage temperature range	-55 to 125		
$R_{thJ-C}$ Thermal resistance, junction to case	0.019 0.0095	K/W	DC operation single side cooled DC operation double side cooled
$R_{th(C-h)}$ Thermal resistance, case to heatsink	0.004 0.002	K/W	Single side cooled Double side cooled
F Mounting force $\pm 10\%$	43000 (4400)	N (Kg)	Clamping force 43KN with mounting compound
wt Approximate weight	1600	g	
Case style	(R-PUK)		See Outline Table

### $\Delta R_{thJ-C}$ Conduction

(The following table shows the increment of thermal resistance  $R_{thJ-C}$  when devices operate at different conduction angles than DC)

Conduction angle	Single side	Double side	Units	Conditions
180°	0.0010	0.0010	K/W	$T_J = T_{J\max}$
120°	0.0017	0.0017		
60°	0.0044	0.0044		

## ST2600C..R Series

### Ordering Information Table

Device Code														
1	ST	2	60	3	0	4	C	5	30	6	R	7	1	8
<b>1</b>	- Thyristor													
<b>2</b>	- Essential part number													
<b>3</b>	- 0 = Converter grade													
<b>4</b>	- C = Ceramic Puk													
<b>5</b>	- Voltage code: Code x 100 = $V_{RRM}$ (See Voltage Rating Table)													
<b>6</b>	- R = Puk Case													
<b>7</b>	- 0 = Eyelet terminals (Gate and Auxiliary Cathode Unsoldered Leads)													
	1 = Fast-on terminals (Gate and Auxiliary Cathode Unsoldered Leads)													
	2 = Eyelet terminals (Gate and Auxiliary Cathode Soldered Leads)													
	3 = Fast-on terminals (Gate and Auxiliary Cathode Soldered Leads)													
<b>8</b>	- Critical dv/dt: None = 500V/ $\mu$ sec (Standard selection)													
	L = 1000V/ $\mu$ sec (Special selection)													

### Outline Table

