


DESCRIPTION:

FEATURES:

- ## MAXIMUM RATINGS

I_C	18.75 A
V_{CC}	55 V
P_{DISS}	730 W @ T _C = 25 °C
T_J	-65 °C to +250 °C
T_{STG}	-65 °C to +200 °C
θ_{JC}	0.24 °C/W

PACKAGE STYLE .400 2L FLG(A)



DIM	W	
	MINIMUM inches / mm	MAXIMUM inches / mm
A	.135 / 3.43	.145 / 3.68
B	.100 / 2.54	.120 / 3.05
C	.050 / 1.27	
D	.376 / 9.55	.396 / 10.06
E	.110 / 2.79	.130 / 3.30
F	.395 / 10.03	.407 / 10.34
G	.193 / 4.90	
H	.490 / 12.45	.510 / 12.95
I	.100 / 2.54	
J	.690 / 17.53	.710 / 18.03
K	.890 / 22.61	.910 / 23.11
L	.003 / 0.08	.006 / 0.18
M	.052 / 1.32	.072 / 1.83
N	.118 / 3.00	.131 / 3.33
P		.230 / 5.84

CHARACTERISTICS $T_C = 25\text{ }^{\circ}\text{C}$

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CBO}	I _C = 50 mA	65			V
BV_{CES}	I _C = 50 mA	65			V
BV_{EBO}	I _E = 15 mA	3.0			V
I_{CES}	V _{CE} = 50 V			30	mA
h_{FE}	V _{CE} = 5.0 V I _C = 5.0 A	10		---	---
P_G	V _{CC} = 50 V P _{IN} = 63 W f = 1235 to 1365 MHz	6.3	6.8		dB
η_c		40	45		%
P_{OUT}		270	300		W