



400mA Super LDO Linear Regulator

CYT6119

Description


The CYT6119 is an efficient linear voltage regulator. It has extra low dropout voltage. At light loads the typical dropout voltage is 15mV, at full load the typical dropout voltage is 600mV. The output voltage accuracy is better than 2%.

The CYT6119 has low ground current at 65uA, so it can help prolong battery life. The CYT6119 is specially designed for hand-held, battery-powered devices.

Features

- Typical 175mV dropout voltage at 150mA.
- Low Ground current at 65uA. (Typ.)
- Guaranteed 400mA output over the full operating temperature range.
- Extremely tight load and line regulation.
- Low temperature coefficient.
- Current and thermal limiting.
- No-load stability.
- Standard SOT-89-3 package.


Pin Configuration




Applications

- Active SCSI terminators.
- Post regulators for switching supplies.
- Battery chargers.
- High-efficiency linear power supplies.
- Computer motherboard, display, graphic card DC/DC converter, such as 5V to 3.3V, 3.3V to 2.8V or 3.3V to 2.5V.

Typical Application



Ordering Information





400mA Super LDO Linear Regulator

CYT6119

Absolute Maximum Ratings⁽¹⁾

Supply Input Voltage (V_{IN})+6V
 Power Dissipation (P_D) Internally Limited ⁽³⁾
 Junction Temperature (T_J) 150°C
 Lead Temperature (soldering, 5 sec.) 260°C
 Storage Temperature (T_S) -10°C to +150°C

Operating Ratings⁽²⁾

Supply Input Voltage (V_{IN}) +2.8V to +5.5V
 Junction Temperature (T_J) 0°C to +125°C
 Package Thermal Resistance 180°C/W

Electrical Characteristics

$V_{IN} = V_{OUT} + 1.0V$; $C_{IN} = 2.2\mu F$; $C_{OUT} = 2.2\mu F$, $I_{OUT} = 10mA$; $T_J = 25^\circ C$, unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Units
V_{OUT}	Output Voltage Accuracy	CYT6119-1.5V	1.470	1.5	1.530	V
		CYT6119-1.8V	1.764	1.8	1.836	
		CYT6119-2.5V	2.450	2.5	2.550	
		CYT6119-2.8V	2.744	2.8	2.856	
		CYT6119-3.0V	2.940	3.0	3.060	
		CYT6119-3.3V	3.234	3.3	3.366	
$\Delta V_{OUT} / \Delta T$	Output Voltage Temperature Coefficient	Note 4	--	50	--	ppm/°C
$\Delta V_{OUT} / V_{OUT}$	Line Regulation	$V_{IN} = V_{OUT} + 1V$ to 5.5V	--	1	--	%
$\Delta V_{OUT} / V_{OUT}$	Load Regulation ⁽⁵⁾	$I_{OUT} = 10mA$ to 250mA ⁽⁵⁾	--	1	--	%
		$I_{OUT} = 10mA$ to 400mA ⁽⁵⁾	--	1.5	--	
$V_{IN} - V_{OUT}$	Dropout Voltage ⁽⁶⁾	$I_{OUT} = 10mA$	--	15	--	mV
		$I_{OUT} = 150mA$	--	175	--	
		$I_{OUT} = 250mA$	--	320	--	
		$I_{OUT} = 400mA$	--	600	--	
$T_{PROTECTION}$	Thermal Protection	Thermal Protection Temperature	--	150	--	°C
		Protection Hysterisys	--	20	--	°C
PSRR	Ripple Rejection	$f = 120Hz$	--	51	--	dB
I_{GROUND}	Ground Current	$I_{OUT} = 10mA$	--	65	--	uA
		$I_{OUT} = 400mA$	--	110	--	
I_{LIMIT}	Current Limit	$V_{OUT} = 0V$	--	600	--	mA



400mA Super LDO Linear Regulator

CYT6119

Note 1: Exceeding the absolute maximum rating may damage the device.

Note 2: The device is not guaranteed to function outside its operating rating.

Note 3: The maximum allowable power dissipation at any TA (ambient temperature) is calculated using: $P_{D(MAX)} = (T_{J(MAX)} - T_A)/\theta_{JA}$. Exceeding the maximum allowable power dissipation will result in excessive die temperature, and the regulator will go into thermal shutdown. See Table 1 and the “Thermal Considerations” section for details.

Note 4: Output voltage temperature coefficient is the worst-case voltage change divided by the total temperature range.

Note 5: Regulation is measured at constant junction temperature using low duty cycle pulse testing. Parts are tested for load regulation in the load range from 100 μ A to 400mA. Changes in output voltage due to heating effects are covered by the thermal regulation specification.

Note 6: Dropout voltage is defined as the input to output differential at which the output voltage drops 2% below its nominal value measured at 1V differential.



Application Hints

Like any Low dropout regulator, CYT6119 requires external capacitors to ensure stability. The external capacitors must be carefully selected to ensure the performances.

Input Capacitor:

An Input Capacitor of at least 10uF is required.

Ceramic or Tantalum can be used. The value can be increased without upper limit.

Output Capacitor:

An Output Capacitor is required for look stability. It must be located no more than 1cm away from the V_{OUT} pin, and connected directly between V_{OUT} and GND pins. The minimum value is 10uF but once again its value can be increased without limit.

Thermal Consideration

It is important that the thermal limit of the package should not be exceeded. The CYT6119 has built-in thermal protection. When the thermal limit is exceeded, the IC will enter protection, and the V_{OUT} will be reset to zero. The power dissipation for a given application can be calculated as follows:

The Power Dissipation (P_D) is

$$P_D = I_{OUT} * [V_{IN} - V_{OUT}]$$

The thermal limit of the package is then limited to

$P_{D(MAX)} = [T_J - T_A]/\theta_{JA}$ where T_J is the junction temperature, T_A is ambient temperature, and θ_{JA} is around 180°C/W for CYT6119. CYT6119 is designed to enter thermal protection at 150°C. For example, if T_A is 25°C then the max P_D is limited to about 0.7W. In other words, if $I_{OUT(MAX)} = 400mA$, then $[V_{IN} - V_{OUT}]$ can not exceed 1.75V.









400mA Super LDO Linear Regulator

CYT6119


Typical Performance Characteristics

($V_{IN} = 5V$, $C_{IN} = 1\mu F$, $C_{OUT} = 10\mu F$, $T_A = 25^\circ C$, unless otherwise noted.)





Outline Drawing for SOT-89



DIMENSIONS				
DIM ^N	INCHES		MM	
	MIN	MAX	MIN	MAX
A	0.173	0.181	4.400	4.600
B	0.159	0.167	4.050	4.250
C	0.067	0.075	1.700	1.900
D	0.051	0.059	1.300	1.500
E	0.094	0.102	2.400	2.600
F	0.035	0.047	0.890	1.200
G	0.118REF		3.00REF	
H	0.059REF		1.50REF	
I	0.016	0.020	0.400	0.520
J	0.055	0.063	1.400	1.600
K	0.014	0.016	0.350	0.410
L	10°TYP		10°TYP	
M	0.028REF		0.70REF	