

## Axial lead diode

### Standard silicon rectifier diodes

#### 1N 5391...1N 5399

**Forward Current: 1,5 A**

**Reverse Voltage: 50 to 1000 V**

### Features

- Max. solder temperature: 260°C
- Plastic material has UL classification 94V-0

### Mechanical Data

- Plastic case DO-15 / DO-204AC
- Weight approx.: 0.4 g
- Terminals: plated terminals solderable per MIL-STD-750
- Mounting position: any
- Standard packaging: 4000 pieces per ammo

1) Valid, if leads are kept at ambient temperature at a distance of 10 mm from case


2)  $I_F = 1,5\text{A}$ ,  $T_j = 25^\circ\text{C}$

3)  $T_A = 25^\circ\text{C}$

Type	Repetitive peak reverse voltage $V_{RRM}$ V	Surge peak reverse voltage $V_{RSM}$ V	Max. reverse recovery time $t_{rr}$ ns	Max. forward voltage $V_F^2)$
1N 5391	50	100	-	1,3
1N 5392	100	200	-	1,3
1N 5393	200	300	-	1,3
1N 5394	300	400	-	1,3
1N 5395	400	500	-	1,3
1N 5396	500	600	-	1,3
1N 5397	600	800	-	1,3
1N 5398	800	1000	-	1,3
1N 5399	1000	1200	-	1,3

Absolute Maximum Ratings		$T_c = 25^\circ\text{C}$ , unless otherwise specified	
Symbol	Conditions	Values	Units
$I_{FAV}$	Max. averaged fwd. current, R-load, $T_A = 50^\circ\text{C}$ <sup>1)</sup>	1,5	A
$I_{FRM}$	Repetitive peak forward current $f > 15\text{ Hz}^1)$	10	A
$I_{FSM}$	Peak forward surge current 50 Hz half sinus-wave <sup>3)</sup>	50	A
$i^2t$	Rating for fusing, $t < 10\text{ ms}^3)$	12,5	A <sup>2</sup> s
$R_{thA}$	Max. thermal resistance junction to ambient <sup>1)</sup>	45	K/W
$R_{thT}$	Max. thermal resistance junction to terminals <sup>1)</sup>	-	K/W
$T_j$	Operating junction temperature	-50...+175	°C
$T_s$	Storage temperature	-50...+175	°C

Characteristics		$T_c = 25^\circ\text{C}$ unless otherwise specified	
Symbol	Conditions	Values	Units
$I_R$	Maximum leakage current, $T_j = 25^\circ\text{C}$ ; $V_R = V_{RRM}$	<10	µA
	$T_j = 100^\circ\text{C}$ ; $V_R = V_{RRM}$	<50	µA
$C_J$	Typical junction capacitance (at MHz and applied reverse voltage of V)	-	pF
$Q_{rr}$	Reverse recovery charge ( $U_R = V$ ; $I_F = A$ ; $dI_F/dt = A/\text{ms}$ )	-	µC
$E_{RSM}$	Non repetitive peak reverse avalanche energy ( $I_R = \text{mA}$ ; $T_j = {}^\circ\text{C}$ ; inductive load switched off)	-	mJ



# 1N 5391...1N 5399




Fig. 1 Forward characteristics ( typical values )




Fig. 2 Rated forward current vs. ambient temperature <sup>1)</sup>




Fig. 3  $I_{FSM}$  current versus number of cycles at 50 Hz