



ALPHA & OMEGA
SEMICONDUCTOR



AO6802

Dual N-Channel Enhancement Mode Field Effect Transistor



General Description

The AO6802 uses advanced trench technology to provide excellent $R_{DS(ON)}$ and low gate charge. This device is suitable for use as a load switch or in PWM applications. Standard Product AO6802 is Pb-free (meets ROHS & Sony 259 specifications). AO6802L is a Green Product ordering option. AO6802 and AO6802L are electrically identical.

Features

V_{DS} (V) = 30V
 I_D = 3.1 A (V_{GS} = 10V)
 $R_{DS(ON)} < 75\text{m}\Omega$ (V_{GS} = 10V)
 $R_{DS(ON)} < 115\text{m}\Omega$ (V_{GS} = 4.5V)

TSOP6
Top View



Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	Maximum		Units
Drain-Source Voltage	V_{DS}	30		V
Gate-Source Voltage	V_{GS}	± 20		V
Continuous Drain Current ^A	I_D	3.1		A
$T_A=70^\circ\text{C}$		2.4		
Pulsed Drain Current ^B	I_{DM}	12		
Power Dissipation ^A	P_D	1.15		W
$T_A=70^\circ\text{C}$		0.73		
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150		°C

Thermal Characteristics each FET

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient ^A	$R_{\theta JA}$	78	110	°C/W
Steady-State		106	150	°C/W
Maximum Junction-to-Lead ^C	$R_{\theta JL}$	64	80	°C/W

N-Channel Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	$I_D=250\mu\text{A}, V_{\text{GS}}=0\text{V}$	30			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{\text{DS}}=24\text{V}, V_{\text{GS}}=0\text{V}$ $T_J=55^\circ\text{C}$			1	μA
I_{GSS}	Gate-Body leakage current	$V_{\text{DS}}=0\text{V}, V_{\text{GS}}=\pm20\text{V}$			5	nA
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	$V_{\text{DS}}=V_{\text{GS}}, I_D=250\mu\text{A}$	1	1.9	3	V
$I_{\text{D(ON)}}$	On state drain current	$V_{\text{GS}}=10\text{V}, V_{\text{DS}}=5\text{V}$	12			A
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{\text{GS}}=10\text{V}, I_D=3.1\text{A}$ $T_J=125^\circ\text{C}$		54	75	$\text{m}\Omega$
		$V_{\text{GS}}=4.5\text{V}, I_D=2\text{A}$		78		
g_{FS}	Forward Transconductance	$V_{\text{DS}}=5\text{V}, I_D=3.1\text{A}$		4.5		S
V_{SD}	Diode Forward Voltage	$I_S=1\text{A}$		0.79	1	V
I_S	Maximum Body-Diode Continuous Current				2.5	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=15\text{V}, f=1\text{MHz}$		200	240	pF
C_{oss}	Output Capacitance			40		pF
C_{rss}	Reverse Transfer Capacitance			20		pF
R_g	Gate resistance	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=0\text{V}, f=1\text{MHz}$		2.3	3	Ω
SWITCHING PARAMETERS						
$Q_g(10\text{V})$	Total Gate Charge	$V_{\text{GS}}=10\text{V}, V_{\text{DS}}=15\text{V}, I_D=3.1\text{A}$		6.5	8.5	nC
$Q_g(4.5\text{V})$	Total Gate Charge			3.1	4	nC
Q_{gs}	Gate Source Charge			1.2		nC
Q_{gd}	Gate Drain Charge			1.6		nC
$t_{\text{D(on)}}$	Turn-On DelayTime	$V_{\text{GS}}=10\text{V}, V_{\text{DS}}=15\text{V}, R_L=4.7\Omega, R_{\text{GEN}}=3\Omega$		3.3		ns
t_r	Turn-On Rise Time			2.5		ns
$t_{\text{D(off)}}$	Turn-Off DelayTime			13.2		ns
t_f	Turn-Off Fall Time			1.7		ns
t_{rr}	Body Diode Reverse Recovery Time	$I_F=3.1\text{A}, dI/dt=100\text{A}/\mu\text{s}$		9.4	12	ns
Q_{rr}	Body Diode Reverse Recovery Charge	$I_F=3.1\text{A}, dI/dt=100\text{A}/\mu\text{s}$		3.5		nC

A: The value of R_{0JA} is measured with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ\text{C}$.

The value in any given application depends on the user's specific board design. The current rating is based on the $t \leq 10\text{s}$ thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The R_{0JA} is the sum of the thermal impedance from junction to lead R_{0JL} and lead to ambient.

D. The static characteristics in Figures 1 to 6,12,14 are obtained using 80 μs pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ\text{C}$. The SOA curve provides a single pulse rating.

Rev 1 : June 2005

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.


N-Channel Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise noted)

Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics


N-Channel Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise noted)

Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance