




- ▼ Capable of 2.5V gate drive
- ▼ Small outline package
- ▼ RoHS Compliant




BV_{DSS}	30V
$R_{DS(ON)}$	720m Ω
I_D	1A

Description

Advanced Power MOSFETs utilized advanced processing techniques to achieve the lowest possible on-resistance, extremely efficient and cost-effectiveness device.

The SOT-23 package is universally used for all commercial-industrial applications.



Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	30	V
V_{GS}	Gate-Source Voltage	± 16	V
$I_D @ T_A = 25^\circ C$	Continuous Drain Current ³ , V_{GS} @ 4.5V	1	A
$I_D @ T_A = 70^\circ C$	Continuous Drain Current ³ , V_{GS} @ 4.5V	0.8	A
I_{DM}	Pulsed Drain Current ^{1,2}	2	A
$P_D @ T_A = 25^\circ C$	Total Power Dissipation	1.38	W
	Linear Derating Factor	0.01	W/ $^\circ C$
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ C$
T_J	Operating Junction Temperature Range	-55 to 150	$^\circ C$

Thermal Data

Symbol	Parameter	Value	Unit
Rthj-a	Thermal Resistance Junction-ambient ³ Max.	90	$^\circ C/W$



AP2318GEN

Electrical Characteristics @ $T_j=25^{\circ}\text{C}$ (unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	30	-	-	V
$\Delta BV_{DSS}/\Delta T_j$	Breakdown Voltage Temperature Coefficient	Reference to 25°C , $I_D=1\text{mA}$	-	0.04	-	$V/^{\circ}\text{C}$
$R_{DS(ON)}$	Static Drain-Source On-Resistance	$V_{GS}=4V, I_D=500\text{mA}$	-	-	720	$\text{m}\Omega$
		$V_{GS}=2.5V, I_D=200\text{mA}$	-	-	1200	$\text{m}\Omega$
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	0.4	-	1.3	V
g_{fs}	Forward Transconductance	$V_{DS}=4V, I_D=500\text{mA}$	-	725	-	mS
I_{DSS}	Drain-Source Leakage Current ($T_j=25^{\circ}\text{C}$)	$V_{DS}=30V, V_{GS}=0V$	-	-	-1	μA
		$V_{DS}=24V, V_{GS}=0V$	-	-	-25	μA
I_{GSS}	Gate-Source Leakage	$V_{GS}=\pm 16V$	-	-	± 30	μA
Q_g	Total Gate Charge ²	$I_D=1A$	-	1.1	1.8	nC
Q_{gs}	Gate-Source Charge	$V_{DS}=25V$	-	0.4	-	nC
Q_{gd}	Gate-Drain ("Miller") Charge	$V_{GS}=4.5V$	-	0.4	-	nC
$t_{d(on)}$	Turn-on Delay Time ²	$V_{DS}=15V$	-	17	-	ns
t_r	Rise Time	$I_D=1A$	-	44	-	ns
$t_{d(off)}$	Turn-off Delay Time	$R_G=3.3\Omega, V_{GS}=5V$	-	45	-	ns
t_f	Fall Time	$R_D=15\Omega$	-	55	-	ns
C_{iss}	Input Capacitance	$V_{GS}=0V$	-	30	48	pF
C_{oss}	Output Capacitance	$V_{DS}=25V$	-	12	-	pF
C_{riss}	Reverse Transfer Capacitance	$f=1.0\text{MHz}$	-	11	-	pF

Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_{SD}	Forward On Voltage ²	$I_S=1A, V_{GS}=0V$	-	-	1.3	V

Notes:

1. Pulse width limited by Max. junction temperature.
2. Pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.
3. Surface mounted on 1 in^2 copper pad of FR4 board ; 270°C/W when mounted on min. copper pad.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance v.s. Gate Voltage




Fig 4. Normalized On-Resistance v.s. Junction Temperature




Fig 5. Forward Characteristic of Reverse Diode




Fig 6. Gate Threshold Voltage v.s. Junction Temperature




Fig 7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig 10. Effective Transient Thermal Impedance




Fig 11. Transfer Characteristics




Fig 12. Gate Charge Circuit