





E-Series 75 Ohm Coupler 5 - 1000 MHz

Features

- Coupling 8db Typical
- Surface Mount
- Low Profile
- Tape and Reel Packaging available



SM-55 Package



Description

M/A-COM's ELDC-8X1 is a high performance 75 Ohm Coupler, in a SM-55 low cost, surface mount package. The ELDC-8 is designed for use in high volume CATV applications. Typical applications include Set-top Boxes, Network Interface Units, Line Amplifiers and Headend equipment.

Electrical Specifications @25°C, Z₀ = 75 Ohms

Frequency Range	Units	Nominal	Typical	Minimum	Maximum
Mainline Loss	5 - 870 MHz	—	1.9	—	2.1
	870 - 1000 MHz	—	2.1	—	2.3
Coupling	5 - 870 MHz	8.5	—	—	± 0.5
	870 - 1000 MHz	7.9	—	—	± 0.5
Coupling Flatness	dB	—	—	—	0.9
Directivity	5 - 870 MHz	—	14.5	12.5	—
	870 - 1000 MHz	—	13.5	11.5	—
Input Return Loss	5 - 50 MHz	—	19.0	18.0	—
	50 - 870 MHz	—	19.5	17.5	—
	870 - 1000 MHz	—	22.0	18.5	—
Output Return Loss	5 - 50 MHz	—	27.0	25.5	—
	50 - 870 MHz	—	28.0	24.5	—
	870 - 1000 MHz	—	28.5	24.0	—
Coupled Return Loss	5 - 50 MHz	—	18.0	16.5	—
	50 - 870 MHz	—	18.5	17.0	—
	870 - 1000 MHz	—	23.0	19.0	—


S 1419 C



M/A-COM Division of AMP Incorporated ■ North America: Tel. (800) 366-2266, Fax (800) 618-8883 ■ Asia/Pacific: Tel. +85 2 2111 8088, Fax +85 2 2111 8087 ■ Europe: Tel. +44 (1344) 869 595, Fax+44 (1344) 300 020

www.macom.com

AMP and Connecting at a Higher Level are trademarks.
Specifications subject to change without notice.



Operating Characteristics


Function	Pin No.
Input	6
Output	1
Coupled	4
External 75 Ohms	3
Ground	5
Not Connected	2

Absolute Maximum Ratings


Parameter	Absolute Maximum
RF Power	250 mW
DC Current	30 mA
Pin Temperature (10 sec)	260°C
Operating/Storage Temperature	-40°C to +85°C

Typical Performance @ 25°C


Insertion Loss




Coupled Port Return Loss




Coupling




Output Return Loss



Directivity



Input Return Loss



S 1419 C



M/A-COM Division of AMP Incorporated ■ North America: Tel. (800) 366-2266, Fax (800) 618-8883 ■ Asia/Pacific: Tel. +85 2 2111 8088, Fax +85 2 2111 8087 ■ Europe: Tel. +44 (1344) 869 595, Fax+44 (1344) 300 020

www.macom.com

AMP and Connecting at a Higher Level are trademarks. Specifications subject to change without notice.

