



PIN NO	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
SEGMENT	COM	≡	B-C	NC	NC	NC	NC	4DP	3E	3D	3C	3DP	2E	2D	2C	2DP	1E	1D	1C	1B
PIN NO	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
SEGMENT	1A	1F	1G	2B	2A	2F	2G	COL	3B	3A	3F	3G	NC	NC	NC	NC	NC	LO BAT	≡	COM

NOTES:

- 1: TOLERANCES UNLESS OTHERWISE SPECIFIED:  $\pm 0.20$
- 2: VIEWING ANGLE: 6 O'CLOCK
- 3: POLARIZER: REFLECTIVE
- 4: DUTY: STATIC
- 5: DRIVING VOLTAGE: 5V
- 6: OPERATING TEMPERATURE: 0°C TO +55°C
- 7: STORAGE TEMPERATURE: -15°C TO +65°C

AZ Displays, Inc.		
DRAWN BY: Y. Q. L	TITLE: 3.5 Digit	SCALE:
CHECKED BY: H.L.P		UNIT: MM
Part No.	GD-057BP	SIZE: A4
DATE: NOV 6, 1997	SHEET 1	OF 1