


TRIPLE DIFFUSED SILICON NPN TRANSISTOR

... designed for low frequency power amplifier

MAXIMUM RATINGS

Characteristic	Symbol	Value	Unit
Collector Base Voltage	V_{CBO}	100	V
Collector Emitter Voltage	V_{CEO}	80	V
Emitter Base Voltage	V_{EBO}	5	V
Collector Current (DC)	I_C	4	A
Collector Current (Peak)	I_C	8	A
Collector power Dissipation	P_C	40	W
Junction Temperature	T_J	150	°C
Storage Temperature	T_{stg}	-55~150	°C



ELECTRICAL CHARACTERISTICS


Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector Cut Off Current	I_{CBO}	$V_{CB} = 80V, I_E = 0A$	-	-	100	μA
Collector – Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 50mA, I_B = 0A$	80	-	-	V
DC Current Gain	h_{FE}	$V_{CE} = 4V, I_C = 1A$	60	-	200	-
		$V_{CE} = 4V, I_C = 0.1A$	35	-	-	-
Collector Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 2A, I_B = 0.2A$	-	-	1	V
Base Emitter Voltage	V_{BE}	$V_{CE} = 4V, I_C = 1A$	-	-	1.5	V
Transition Frequency	f_T	$V_{CE} = 5V, I_C = 0.5A$	-	10	-	MHz
Collector Out put Capacitance	C_{ob}	$V_{CB} = 20V, I_E = 0A, f=1MHz$	-	40	-	Pf

HIGH POWER DISSIPATION

MEDIUM SPEED POWER SWITCHING

Classification of h_{FE}

Rank	B	C
Range	60 to 120	100-200



PMC reserves the right to make changes without further notice to any products herein. **PMC** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **PMC** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential damages. The examples of applied circuits are provided as reference to the reader therefore we shall not undertake any responsibility for the exercise of rights by third parties.