


## 2 INPUT NOR GATE


## FEATURES

- High output drive :  $\pm 24\text{mA}(\text{min.})$  @  $V_{CC}=3\text{V}$ .
- Super high speed operation :  $t_{pd} 2.4\text{ns}(\text{typ.})$  @  $V_{CC}=5\text{V}$ ,  $50\text{pF}$ .
- Operation voltage range :  $V_{CC(\text{opr})}=1.65\text{~}5.5\text{V}$ .
- Power down protection is provided on all inputs and outputs.


## MARKING

MAXIMUM RATINGS ( $T_a=25^\circ\text{C}$ )

CHARACTERISTIC	SYMBOL	RATING	UNIT
Power Supply Voltage	$V_{CC}$	-0.5~7	V
DC Input Voltage	$V_{IN}$	-0.5~7	V
DC Output Voltage	$V_{OUT}$	-0.5~7	V
Input Diode Current	$I_{IK}$	-50	mA
Output Diode Current	$I_{OK}$	-50	mA
DC Output Current	$I_{OUT}$	$\pm 50$	mA
DC $V_{CC}$ /ground Current	$I_{CC}$	$\pm 100$	mA
Power Dissipation	$P_D$	200	mW
Storage Temperature Range	$T_{stg}$	-55 ~ 150	°C
Lead Temperature (10s)	$T_L$	-55 ~ 150	°C



## PIN CONNECTION(TOP VIEW)




# KIC7WZ02FK

Truth Table

A	B	Y
L	L	H
L	H	L
H	L	L
H	H	L

Logic Diagram



Recommended Operating Conditions

CHARACTERISTIC	SYMBOL	RATING	UNIT
Supply Voltage	V <sub>CC</sub>	1.65~5.5	V
		1.5~5.5 (Note1)	
Input Voltage	V <sub>IN</sub>	0~5.5	V
Output Voltage	V <sub>OUT</sub>	0~5.5 (Note2)	V
		0~V <sub>CC</sub> (Note3)	
Operating Temperature	T <sub>opr</sub>	-40~85	°C
Input Rise and Fall Time	d <sub>r/d<sub>v</sub></sub>	0~20 (V <sub>CC</sub> =1.8V ± 0.15V, 2.5V ± 0.2V)	ns/V
		0~10 (V <sub>CC</sub> =3.3V ± 0.3V)	
		0~5 (V <sub>CC</sub> =5.5V ± 0.5V)	

Note1 : Data retention only.

Note2 : V<sub>CC</sub>=0V.

Note3 : High or low state

# KIC7WZ02FK

## ELECTRICAL CHARACTERISTICS

### DC Characteristics

CHARACTERISTIC	SYMBOL	TEST CONDITION		Ta=25 °C			Ta=-40~85 °C		UNIT		
			V <sub>CC</sub> (V)	MIN.	TYP.	MAX.	MIN.	MAX.			
Input Voltage	High Level	V <sub>IH</sub>	-	1.65~1.95	0.75 × V <sub>CC</sub>	-	-	0.75 × V <sub>CC</sub>	-	V	
				2.3~5.5	0.7 × V <sub>CC</sub>	-	-	0.7 × V <sub>CC</sub>	-		
	Low Level	V <sub>IL</sub>	-	1.65~1.95	-	-	0.25 × V <sub>CC</sub>	-	0.25 × V <sub>CC</sub>		
				2.3~5.5	-	-	0.3 × V <sub>CC</sub>	-	0.3 × V <sub>CC</sub>		
Output Voltage	High Level	V <sub>OH</sub>	V <sub>IN</sub> =V <sub>IL</sub>	I <sub>OH</sub> =-100 μA	1.65	1.55	1.65	-	1.55	V	
					2.3	2.2	2.3	-	2.2		
					3.0	2.9	3.0	-	2.9		
					4.5	4.4	4.5	-	4.4		
				I <sub>OH</sub> =-4mA	1.65	1.29	1.52	-	1.29		
					I <sub>OH</sub> =-8mA	2.3	1.9	2.15	-	1.9	
					I <sub>OH</sub> =-16mA	3.0	2.4	2.8	-	2.4	
					I <sub>OH</sub> =-24mA	3.0	2.3	2.68	-	2.3	
	Low Level	V <sub>OL</sub>	V <sub>IN</sub> =V <sub>IH</sub>	I <sub>OH</sub> =100 μA	4.5	3.8	4.2	-	3.8	V	
					1.8	-	0	0.1	-		
					2.3	-	0	0.1	-		
					3.0	-	0	0.1	-		
				I <sub>OH</sub> =4mA	4.5	-	0	0.1	-		
					I <sub>OH</sub> =8mA	1.65	-	0.08	0.24		
					I <sub>OH</sub> =16mA	2.3	-	0.1	0.3		
					I <sub>OH</sub> =24mA	3.0	-	0.15	0.4		
					I <sub>OH</sub> =32mA	3.0	-	0.22	0.55		
					I <sub>OH</sub> =32mA	4.5	-	0.22	0.55		
Input Leakage Current	I <sub>IN</sub>	V <sub>IN</sub> =5.5V or GND		0~5.5	-	-	±0.1	-	±10	μA	
Power Off Leakage Current	I <sub>OFF</sub>	V <sub>IN</sub> or V <sub>OUT</sub> =5.5V		0.0	-	-	1	-	10	μA	
Quiescent Supply Current	I <sub>CC</sub>	V <sub>IN</sub> =5.5V or GND		1.65~5.5	-	-	1	-	10	μA	


AC Characteristics (unless otherwise specified, Input : t<sub>r</sub>=t<sub>f</sub>=3ns)

CHARACTERISTIC	SYMBOL	TEST CONDITION		Ta=25 °C			Ta=-40~85 °C		UNIT
			V <sub>CC</sub> (V)	MIN.	TYP.	MAX.	MIN.	MAX.	
Propagation delay time	t <sub>PLH</sub>	C <sub>L</sub> =15pF, R <sub>L</sub> =1M Ω	1.8 ±0.15	2.0	5.4	9.8	2.0	10	ns
			2.5 ±0.2	1.2	3.3	5.4	1.2	5.8	
			3.3 ±0.3	0.8	2.5	3.8	0.8	4.1	
			5.0 ±0.5	0.5	2.0	3.0	0.5	3.3	
	t <sub>PHL</sub>	C <sub>L</sub> =50pF, R <sub>L</sub> =500 Ω	3.3 ±0.3	1.2	3.1	4.6	1.2	5.0	ns
			5.0 ±0.5	0.8	2.4	3.7	0.8	4.0	
Input Capacitance	C <sub>IN</sub>	-		0	-	2.5	-	-	pF
Power Dissipation Capacitance	C <sub>PD</sub>	(Note)	3.3	-	13.5	-	-	-	pF
			5.5	-	17.5	-	-	-	

Note : C<sub>PD</sub> is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation : I<sub>CC(opr)</sub>=C<sub>PD</sub> · V<sub>CC</sub> · f<sub>IN</sub>+(I<sub>CC</sub><sub>static</sub>)


# KIC7WZ02FK

## AC Loading and Waveforms



$C_L$  includes load and stray capacitance  
Input PRR=1.0MHz ;  $t_w$ =500ns

FIGURE 1. AC Test Circuit



Input=AC Waveform ;  $t_r=t_f=1.8ns$   
PRR=10MHz ; Duty Cycle=50%

FIGURE 2. ICCD Test Circuit




FIGURE 3. AC Waveforms