


Low EMI Spread Spectrum Multiplier Clock

FEATURES

- Spread Spectrum Clock Generator with selectable multiplier (1x, 2x, 2.94x and 4x).
- Reference input frequency: 16MHz-60MHz.
- Output frequency ranges: 16MHz to 200MHz.
- Center Spread Modulation.
- TTL/CMOS compatible outputs.
- 3.3V Operating Voltage.
- Low short term jitter.
- Available in 8-Pin 150mil SOIC.

PIN CONFIGURATION



FIN = 16 ~ 60 Mhz

Note: v: 30kΩ Internal Pull down. ^: 30kΩ Internal Pull up.

DESCRIPTION


The PLL701-17 is a Spread Spectrum Clock Generator designed for the purpose of reducing EMI in high-speed digital systems, with selectable Center Spread modulation magnitude (see table below). The multiplication factor can be selected from 4 multiplier modes. The device operates over a wide range of input frequencies and provides 1x, 2x, 2.94x and 4x modulated clock outputs.

OUTPUT CLOCK (FOUT) SELECTION

S3	S2	S1	S0	FIN Range (MHz)	FOUT	Spread Spectrum Modulation	
						Frequency	Magnitude
0	0	0	0	16 - 40	X1	Fin / 512	±0.75%
0	0	0	1	16 - 40	X1		±1.00%
0	0	1	0	16 - 40	X1		±1.25%
0	0	1	1	16 - 40	X1		±1.50%
0	1	0	0	16 - 40	X2	Fin / 512	±0.25%
0	1	0	1	16 - 40	X2		±0.50%
0	1	1	0	16 - 40	X2		±0.75%
0	1	1	1	16 - 40	X2		±1.00%
1	0	0	0	24 - 60	X2	Fin / 1024	±1.25%
1	0	0	1	24 - 60	X2		±1.50%
1	0	1	0	24 - 50	X4		±0.25%
1	0	1	1	24 - 50	X4		±0.50%
1	1	0	0	16 - 40	X2.94	Fin / 1000	±0.25%
1	1	0	1	16 - 40	X2.94		±0.50%
1	1	1	0	16 - 40	X2.94		±0.75%
1	1	1	1	16 - 40	X2.94		±1.00%

Low EMI Spread Spectrum Multiplier Clock

BLOCK DIAGRAM



PIN DESCRIPTIONS

Name	Number	Type	Description
FIN	1	I	Input Clock connection. 16MHz to 60MHz.
S2	2	I	Digital control input to select multiplication factor and SST modulation amplitude. Has internal pull-up.
S1	3	I	Digital control input to select multiplication factor and SST modulation amplitude. Has internal pull-up.
S0	4	I	Digital control input to select multiplication factor and SST modulation amplitude. Has internal pull-down.
GND	5	P	Ground connection.
FOUT	6	O	SST Modulated Clock Output. The frequency before modulation is synthesized by multiplying the input frequency by 1X, 2X, 2.94X or 4X, depending on S(0:3).
S3	7	I	Digital control input to select multiplication factor and SST modulation amplitude. Has internal pull-down.
VDD	8	P	3.3V Power Supply connection.

ELECTRICAL SPECIFICATIONS

1. Absolute Maximum Ratings

PARAMETERS	SYMBOL	MIN.	MAX.	UNITS
Supply Voltage	V _{DD}		4.6	V
Input Voltage, dc	V _I	-0.5	V _{DD} +0.5	V
Output Voltage, dc	V _O	-0.5	V _{DD} +0.5	V
Storage Temperature	T _S	-65	150	°C
Ambient Operating Temperature*	T _A	-40	85	°C
Junction Temperature	T _J		125	°C
Lead Temperature (soldering, 10s)			260	°C
ESD Protection, Human Body Model			2	kV

Exposure of the device under conditions beyond the limits specified by Maximum Ratings for extended periods may cause permanent damage to the device and affect product reliability. These conditions represent a stress rating only, and functional operations of the device at these or any other conditions above the operational limits noted in this specification is not implied.

* **Note:** Operating Temperature is guaranteed by design for all parts (COMMERCIAL and INDUSTRIAL), but tested for COMMERCIAL grade only.

Low EMI Spread Spectrum Multiplier Clock
2. DC/AC Specifications

PARAMETERS	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Supply Voltage	V _{DD}		2.97		3.63	V
Supply Current	I _{DD}	15pF Load, F _{OUT} =16MHz		9		mA
		5pF Load, F _{OUT} =200MHz		25		mA
Input High Voltage	V _{IH}		0.7* V _{DD}			V
Input Low Voltage	V _{IL}				0.3* V _{DD}	V
Input High Current	I _{IH}				100	μA
Input Low Current	I _{IL}				100	μA
Output High Voltage	V _{OH}	I _{OH} =5mA, V _{DD} =3.3V	2.4			
Output Low Voltage	V _{OL}	I _{OL} =6mA, V _{DD} =3.3V			0.4	
Input Frequency	F _{IN}	S3=0 or S3-S2=1-1	16		40	MHz
		S3-S2-S1=1-0-1	24		50	MHz
		S3-S2-S1=1-0-0	24		60	MHz
Recovery from interruption of F _{IN}				1		ms
Input Capacitance	C _{in1}			3		pF
Pull-up Resistor	R _{pu}	PIN 2, 3		30		kΩ
Pull-down Resistor	R _{pd}	PIN 4, 7		30		kΩ
Short Circuit Current	I _{sc}			50		mA
3.3V Dynamic Supply Current	I _{DD}	No Load, F _{OUT} =16MHz		7		mA
		No Load, F _{OUT} =200MHz		21		mA

3. TIMING CHARACTERISTICS

PARAMETERS	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Rise Time	T _r	10%~90%VDD, 15pF Load, F _{OUT} ≤100MHz		2	3	ns
		10%~90%VDD, 10pF Load, F _{OUT} ≤150MHz		1.5	2	ns
		10%~90%VDD, 5pF Load, F _{OUT} ≤200MHz		1	1.5	ns
Fall Time	T _f	90%~10%VDD, 15pF Load, F _{OUT} ≤100MHz		2	3	ns
		90%~10%VDD, 10pF Load, F _{OUT} ≤150MHz		1.5	2	ns
		90%~10%VDD, 5pF Load, F _{OUT} ≤200MHz		1	1.5	ns
Output Duty Cycle	D _T	Measured at 50%VDD	45	50	55	%
Cycle to Cycle Jitter	T _{cyc-cyc}	Over output frequency range @ 3.3V			100	ps peak

Low EMI Spread Spectrum Multiplier Clock

FUNCTIONAL DESCRIPTION

Selectable spread spectrum and modulation frequency and magnitude

The PLL701-17 provides selectable spread spectrum modulation frequency, as well as selectable modulation magnitude. Selection is made by connecting pins 2 (S2), 3 (S1), 4 (S0), and 7 (S3) to a logical “zero” or “one”, according to the output clock selection table on (page 1).

Default values for S(0:3) through internal pull-up and pull-down resistor

Selection pins 4 and 7 (S0 and S3) have an internal pull-down resistor of 30k Ω while pins 2 and 3 (S1 and S2) have an internal pull-up resistor of 30k Ω . This internal pull-down (or pull-up) resistor will pull the input value to a logical “zero” (or “one” respectively) by default, i.e. when no connection is made between the pin and VDD (GND respectively). In order to override the internal pull-down (pull-up), the pin has to be connected to VDD (GND respectively).

Low EMI Spread Spectrum Multiplier Clock

PACKAGE INFORMATION

8 PIN Narrow SOIC (mm)

Symbol	SOIC	
	Min.	Max.
A	1.47	1.73
A1	0.10	0.25
B	0.33	0.51
C	0.19	0.25
D	4.80	4.95
E	3.80	4.00
H	5.80	6.20
L	0.38	1.27
e	1.27 BSC	

ORDERING INFORMATION

For part ordering, please contact our Sales Department:
47745 Fremont Blvd., Fremont, CA 94538, USA
Tel: (510) 492-0990 Fax: (510) 492-0991

PART NUMBER

The order number for this device is a combination of the following:
Device number, Package type and Operating temperature range

PLL701-17 X X X-R

PART NUMBER _____

PACKAGE TYPE _____

S=SOIC

- NONE= TUBE
- R= TAPE AND REEL
- NONE= NORMAL PACKAGE
- L= GREEN PACKAGE
- TEMPERATURE
- C=COMMERCIAL
- I=INDUSTRIAL

Order Number	Marking	Package Option
PLL701-17SC	P701-17SC	SOIC-Tube
PLL701-17SC-R	P701-17SC	SOIC-Tape and Reel
PLL701-17SCL	P701-17SCL	SOIC-Tube (GREEN)
PLL701-17SCL-R	P701-17SCL	SOIC-Tape and Reel (GREEN)

PhaseLink Corporation, reserves the right to make changes in its products or specifications, or both at any time without notice. The information furnished by Phaselink is believed to be accurate and reliable. However, PhaseLink makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of whatever nature resulting from the use of, or reliance upon this product.

LIFE SUPPORT POLICY: PhaseLink's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President of PhaseLink Corporation.