




**S2055AF**


**SILICON DIFFUSED POWER TRANSISTOR**

**GENERAL DESCRIPTION**

Highvoltage,high-speed switching npn transistors in a plastic envelope with integrated efficiency diode , primarily for use in horizontal deflection circuites of colour television receivers



TO-3PM



**QUICK REFERENCE DATA**

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
$V_{CESM}$	Collector-emitter voltage peak value	$V_{BE} = 0V$		1500	V
$V_{CEO}$	Collector-emitter voltage (open base)			600	V
$I_C$	Collector current (DC)			8	A
$I_{CM}$	Collector current peak value			15	A
$P_{tot}$	Total power dissipation	$T_{mb} \leq 25^\circ C$		125	W
$V_{CEsat}$	Collector-emitter saturation voltage	$I_C = 4.5A; I_B = 2.0A$		1.5	V
$I_{csat}$	Collector saturation current	$f = 16KHz$			A
$V_F$	Diode forward voltage	$I_F = 4.0A$		2.0	V
$t_f$	Fall time	$I_C = 4.5A, I_{B1} = -I_{B2} = 1.2A, V_{CC} = 140V$		1.0	$\mu s$

**LIMITING VALUES**

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
$V_{CESM}$	Collector-emitter voltage peak value	$V_{BE} = 0V$		1500	V
$V_{CEO}$	Collector-emitter voltage (open base)			600	V
$V_{EBO}$	Emitter-base voltage(open collector)			5	V
$I_C$	Collector current (DC)			8	A
$I_B$	Base current (DC)			4	A
$I_{BM}$	Base current peak value			6	A
$P_{tot}$	Total power dissipation	$T_{mb} \leq 25^\circ C$		125	W
$T_{stn}$	Storage temperature		-55	150	$^\circ C$
$T_j$	Junction temperature			150	$^\circ C$

**ELECTRICAL CHARACTERISTICS**

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
$I_{CE}$	Collector-emitter cut-off current	$V_{BE} = 0V; V_{CE} = V_{CESMmax}$		1.0	mA
$I_{CES}$		$V_{BE} = 0V; V_{CE} = V_{CESMmax}$		2.0	mA
$V_{CEOsust}$	Collector-emitter sustaining voltage	$T_j = 125^\circ C$ $I_B = 0A; I_C = 100mA$ $L = 25mH$			V
$V_{CEsat}$	Collector-emitter saturation voltages	$I_C = 4.5A; I_B = 2.0A$		1.5	V
$V_{BESat}$	Base-emitter saturation voltage	$I_C = 4.5A; I_B = 2.0A$		2.5	V
$h_{FE}$	DC current gain	$I_C = 1.0A; V_{CE} = 5V$	8	30	
$V_F$	Diode forward voltage	$I_F = 4.5A$		2.0	V
$f_T$	Transition frequency at $f = 1MHz$	$I_C = 0.1A; V_{CE} = 10V$	3		MHz
$C_c$	Collector capacitance at $f = 1MHz$	$V_{CB} = 10V$			pF
$t_s$	Switching times(16KHz line deflecton circuit)	$I_C = 4.5A, I_{B1} = -I_{B2} = 1.2A, V_{CC} = 140V$		7.0	$\mu s$
$t_f$	Turn-off storage time Turn-off fall time	$I_C = 4.5A, I_{B1} = -I_{B2} = 1.2A, V_{CC} = 140V$		1.0	$\mu s$