

# Common Mode Filters(SMD) For High-speed Differential Signal Line

Conformity to RoHS Directive

## TCM Series TCM1005 Type

### FEATURES

- TCM 1005 (L1.0×W0.5×T0.4mm) type is specially the smallest thin product in the industry.
- By providing wide bandwidth (cutoff frequency: 3GHz) for differential mode, this product has almost no effect for high-speed differential signals and can suppress the radiated emission.
- This product contains no lead and supports lead-free soldering.

### APPLICATIONS

- High speed interface(LVDS, IEEE1394 and USB2.0) in electronics devices.
- PDP/LCD/DLP/PJ TV, DVD player, notebook PCs, DVC, DSC, amusement machines, portable audio, digital cellular phones, etc.

### TEMPERATURE RANGE

Operating	-25 to +85°C
-----------	--------------

### PACKAGING STYLE AND QUANTITIES


Packaging style	Quantity
Taping	10000 pieces/reel

### PRODUCT IDENTIFICATION

TCM	1005	-	900	-	2P	-	T
(1)	(2)		(3)		(4)		(5)

- (1) Series name  
 (2) Dimensions L×W  
 (3) Impedance[at 100MHz]  
 900: 90Ω  
 (4) Number of line  
 2P: 2-line  
 (5) Packaging style  
 T: ø180mm reel taping

### SHAPES AND DIMENSIONS/CIRCUIT DIAGRAMS/RECOMMENDED PC BOARD PATTERNS



### ELECTRICAL CHARACTERISTICS

Part No.	Common mode impedance (Ω) [100MHz]	DC resistance (Ω)[1 line]	Rated current Idc(A)max.	Rated voltage Edc(V)max.	Insulation resistance (MΩ)min.
TCM1005-350-2P	35±30%	1.15±30%	0.1	5	10
TCM1005-650-2P	65±20%	2±30%	0.1	5	10
TCM1005-900-2P	90±20%	2.5±30%	0.1	5	10

• Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

• All specifications are subject to change without notice.

### TYPICAL ELECTRICAL CHARACTERISTICS IMPEDANCE vs. FREQUENCY CHARACTERISTICS

