




PHASE NOISE (1 Hz BW, typical)



OFFSET (Hz)

FEATURES

- Frequency Range: 1700 - 1850 MHz
- Tuning Voltage: 0-10 Vdc
- MINI-14S - Style Package

APPLICATIONS

- PCS Basestations
- Portable Test Equipment
- Personal VSATs

PERFORMANCE SPECIFICATIONS	VALUE	UNITS
Oscillation Frequency Range	1700 - 1850	MHz
Phase Noise @ 10 kHz offset (1 Hz BW, typ.)	-102	dBc/Hz
Harmonic Suppression (2nd, typ.)	-7	dBc
Tuning Voltage	0-10	Vdc
Tuning Sensitivity (avg.)	24	MHz/V
Power Output	3.5 ± 2	dBm
Load Impedance	50	Ω
Input Capacitance (max.)	50	pF
Pushing	< 2	MHz/V
Pulling (14 dB Return Loss, Any Phase)	< 2	MHz
Operating Temperature Range	-30 to 70	$^{\circ}\text{C}$
Package Style	MINI-14S	
POWER SUPPLY REQUIREMENTS		
Supply Voltage (Vcc, nom.)	11	Vdc
Supply Current (Icc, typ.)	25	mA


All specifications are typical unless otherwise noted and subject to change without notice.

APPLICATION NOTES


- AN-100/1 : Mounting and Grounding of VCOs
- AN-102 : Proper Output Loading of VCOs
- AN-107 : How to Solder Z-COMM VCOs

NOTES:

TUNING CURVE, typ.



POWER CURVE, typ.



PHYSICAL DIMENSIONS

