

SCHOTTKY BARRIER RECTIFIER

**VOLTAGE RANGE: 30 - 100 V
CURRENT: 10 A**


FEATURES

- ◇ High surge capacity.
- ◇ For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications.
- ◇ Metal silicon junction, majority carrier conduction.
- ◇ High current capacity, low forward voltage drop.
- ◇ Guard ring for over voltage protection.

MECHANICAL DATA

- ◇ Case: JEDEC TO-220AC, molded plastic body
- ◇ Terminals: Leads, solderable per MIL-STD-750, Method 2026
- ◇ Polarity: As marked
- ◇ Position: Any
- ◇ Weight: 0.064 ounces, 1.81 gram

TO-220AC



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

		MBR 1030	MBR 1035	MBR 1040	MBR 1045	MBR 1050	MBR 1060	MBR 1090	MBR 10100	UNITS								
Maximum recurrent peak reverse voltage	V_{RRM}	30	35	40	45	50	60	90	100	V								
Maximum RMS Voltage	V_{RMS}	21	25	28	32	35	42	63	70	V								
Maximum DC blocking voltage	V_{DC}	30	35	40	45	50	60	90	100	V								
Maximum average forward total device rectified current @ $T_c = 125^\circ C$	$I_{F(AV)}$	10								A								
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	150								A								
Maximum forward voltage (I _F =10A, T _C =25°C) (I _F =10A, T _C =125°C) (Note 1) (I _F =20A, T _C =25°C) (I _F =20A, T _C =125°C)	V_F	-		0.80		0.80		0.80		V								
Maximum reverse current @ $T_c = 25^\circ C$ at rated DC blocking voltage @ $T_c = 125^\circ C$	I_R	0.1				15				m A								
Maximum thermal resistance (Note 2)	$R_{\theta JC}$	2.0								°C/W								
Operating junction temperature range	T_J	- 55 ---- + 150								°C								
Storage temperature range	T_{STG}	- 55 ---- + 150								°C								

NOTE: 1. Pulse test: 300μs pulse width, 1% duty cycle.

2. Thermal resistance from junction to case.

3. $T_c=100^\circ C$

www.galaxycn.com

RATINGS AND CHARACTERISTIC CURVES

MBR1030---MBR10100

FIG.1 – FORWARD CURRENT DERATING CURVE




FIG.2 – MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PERLEG




FIG.3 – TYPICAL INSTANTANEOUS FORWARD CHARACTERISTIC PERLEG




FIG.4 – TYPICAL REVERSE CHARACTERISTICS

