

■ Dimensions

Cap. (μF)	Code	4		6.3		10		16		25		35		50		
		0G		0J		1A		1C		1E		1V		1H		
0.1	0R1														4×5.4(3)	1.0
0.22	R22														4×5.4(3)	2.6
0.33	R33														4×5.4(3)	3.2
0.47	R47														4×5.4(3)	3.8
1	010														4×5.4(3)	6.3(5.9)
2.2	2R2											3×5.4	7.5		4×5.4(3)	11(9)
3.3	3R3											3×5.4	9		4×5.4	14
4.7	4R7									4×5.4(3)	13(10)	4×5.4	15		5×5.4	19
10	100							4×5.4(3)	18(14)	5×5.4	23	5×5.4	25		6.3×5.4	30
22	220	4×5.4	22	4×5.4	22	5×5.4	27	5×5.4	30	6.3×5.4	38	6.3×5.4	42	●8×5.4	51(45)	
33	330	5×5.4	30	5×5.4	30	5×5.4	35	6.3×5.4	40	6.3×5.4	48	●8×5.4	59(52)	6.3×7.7	60	
47	470	5×5.4	36	5×5.4	36	6.3×5.4	46	6.3×5.4	50	●8×5.4	66(59)	6.3×5.8	63	6.3×7.7	63	
100	101	6.3×5.4	60	6.3×5.4	60	6.3×5.4	60	6.3×5.4	60	6.3×7.7	91	6.3×7.7	84	8×10	140	
150	151	6.3×5.8	86	6.3×5.8	86	6.3×5.8	86	6.3×7.7	95	8×10	140	8×10	155	10×10	180	
220	221	●8×5.4	102(91)	●8×5.4	102(91)	6.3×7.7	105	6.3×7.7	105	8×10	155	8×10	190	10×10	220	
330	331	6.3×7.7	105	6.3×7.7	105	8×10	195	8×10	195	8×10	190	10×10	300			
470	471	8×10	210	8×10	210	8×10	210	8×10	230	10×10	300					
680	681	8×10	210	8×10	210	10×10	310	10×10	310							
1000	102	8×10	230	8×10	230	10×10	310									
1500	152	10×10	310	10×10	310											

Rated Ripple (mArms) at 105°C 120Hz

() is also available with ø3mm upon request. In such a case, [2] will be put at 12th digit of type numbering system.

Size ø6.3×5.8 is available for capacitors marked. "●" In such a case, [6] will be put at 12th digit of type numbering system.

● Frequency coefficient of rated ripple current

Frequency	50 Hz	120 Hz	300 Hz	1 kHz	10 kHz~
Coefficient	0.70	1.00	1.17	1.36	1.50

- Taping specifications are given in page 24.
- Recommended land size, soldering by reflow are given in page 25, 26.
- Please select UX(p.74), UJ(p.76) series if high C/V products are required.
- Please refer to page 3 for the minimum order quantity.