


DB ELECTRO^{CO., LTD.}

Présente / Presents:

NINGBO HUAGUAN ELECTRONICS CO., LTD.



NT78



15.7×12.3×14



CQC 03001003504
 UL US E160644 on Pending
 Patent No.: 99206529.1
 200520013192.6

Features	
<ul style="list-style-type: none"> Small size, lightweight. Low coil consumption. PC board mounting. Suitable for household electrical appliances, automation system, electronic equipment, instrument, meter, telecommunication facilities and remote control facilities. 	

Ordering Information	
NT78 C S 10 DC12V 0.6	
1 Part number: NT78	4 Contact rating: 5A,10A/14VDC; 10A/120VAC; 5A/250VAC
2 Contact arrangement: A:1A; B:1B; C:1C; U:1U	5 Coil rated voltage(V): DC:6,9,12,24
3 Enclosure: S: Sealed type; NIL: Dust cover	6 Coil power consumption: 0.6:0.6W; 0.8:0.8W

Contact Data	
Contact Arrangement	1A (SPSTNO) 1B (SPSTNC) 1C (SPDT(B-M)) 1U (SPSTNODM)
Contact Material	AgCdO AgSnO ₂ AgSnO ₂ In ₂ O ₃
Contact Rating (resistive)	NO:20A/14VDC 10A/120VAC,5A/250VAC NC:15A/14VDC,10A/120VAC,5A/250VAC IU:2×10A/14VDC Motor load : 1/2HP 125VAC Lamp load : TV-5
Max. Switching Power	280W 1250VA
Max. Switching Voltage	42VDC 380VAC Max. Switching Current:20A
Contact Resistance or Voltage drop	≤50mΩ Item 3.12 of IEC255-7
Operational life	Electrical 10 ⁵ Item 3.30 of IEC255-7
	Mechanical 10 ⁷ Item 3.31 of IEC255-7

Coil Parameter								
Dash numbers	Coil voltage VDC		Coil resistance Ω ±10%	Pickup voltage VDC(max) (80% of rated voltage)	Release voltage VDC(min) (5% of rated voltage)	Coil power consumption W	Operate Time ms	Release Time ms
	Rated	Max.						
006-600	6	6.6	60	4.8	0.30	0.6	≤10	≤5
009-600	9	9.9	135	7.2	0.45			
012-600	12	13.2	240	9.6	0.60			
024-600	24	26.4	960	19.2	1.20			
006-800	6	6.6	45	4.8	0.30	0.8	≤10	≤5
009-800	9	9.9	102	7.2	0.45			
012-800	12	13.2	180	9.6	0.60			
024-800	24	26.4	720	19.2	1.20			

CAUTION: 1.The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.
 2.Pickup and release voltage are for test purposes only and are not to be used as design criteria.

Operation condition		
Insulation Resistance	100MΩ min (at 500VDC)	Item 7 of IEC255-5
Dielectric Strength	Between contacts	50Hz 500V
	Between contact and coil	50Hz 500V
Shock resistance	100m/s ² 11ms	IEC68-2-27 Test Ea
Vibration resistance	10~55Hz double amplitude 1.5mm	IEC68-2-6 Test Fc
Terminals strength	10N	IEC68-2-21 Test Ua1
Solderability	235°C ±2°C 3±0.5s	IEC68-2-20 Test Ta method 1
Ambient Temperature	-40~85°C	
Relative Humidity	85% (at 20°C)	IEC68-2-3 Test Ca
Mass	6g	

Qualification inspection:
 Perform the qualification test as specified in the table IV of IEC255-19-1 and minimum sample size 24.

Safety approval	UL&CUR	CQC
Load	NO: 20A/14VDC 10A/120VAC NC: 10A/14VDC 1/2HP 125VAC TV-5	5A/250VAC

Dimensions

Dimensions (mm / inch)

Mounting (Bottom view)

Wiring diagram (Bottom view)

NOTES 1). Dimensions are in millimeters.
 2). Inch equivalents are given for general information only.

