

# TS7800B Series

## 3-Terminal Fixed Positive Voltage Regulator

TO-220



ITO-220



TO-263  
(D<sup>2</sup>PAK)



**Pin Definition:**

1. Input
2. Ground (tab)
3. Output

### General Description

These voltage regulators are monolithic integrated circuits designed as fixed-voltage regulators for a wide variety of applications including local, on-card regulation. These regulators employ internal current limiting, thermal shutdown, and safe-area compensation. With adequate heatsink they can deliver output currents up to 1 ampere.

Although designed primarily as a fixed voltage regulator, these devices can be used with external components to obtain adjustable voltages and currents.

### Features


- Output Voltage Range 5 to 24V
- Output current up to 1.5A
- No external components required
- Internal thermal overload protection
- Internal short-circuit current limiting
- Output transistor safe-area compensation
- Output voltage offered in 4% tolerance

### Ordering Information

Part No.	Package	Packing
TS78xxBCZ C0	TO-220	50pcs / Tube
TS78xxBCI C0	ITO-220	50pcs / Tube
TS78xxBCM RN	TO-263	800pcs / 13" Reel

Note: Where xx denote voltage option

### Standard Application Circuit



A common ground is required between the input and the output voltages. The input voltage must remain typically 2.0V above the output voltage even during the low point on the Input ripple voltage.

XX = these two digits of the type number indicate voltage.

\* = Cin is required if regulator is located an appreciable distance from power supply filter.

\*\* = Co is not needed for stability; however, it does improve transient response.

### Absolute Maximum Rating (Ta = 25 °C unless otherwise noted)

Parameter	Symbol	Limit	Unit
Input Voltage	V <sub>IN</sub> *	35	V
Input Voltage	V <sub>IN</sub> **	40	V
Power Dissipation	P <sub>D</sub>	Internal Limited	W
Operating Junction Temperature	T <sub>J</sub>	0~+125	°C
Storage Temperature Range	T <sub>STG</sub>	-65~+150	°C

Note: \* TS7805B to TS7818B

\*\* TS7824B

\*\*\* Follow the derating curve

### TS7805B Electrical Characteristics

( $V_{in}=10V$ ,  $I_{out}=500mA$ ,  $0^{\circ}C \leq T_j \leq 125^{\circ}C$ ,  $C_{in}=0.33\mu F$ ,  $C_{out}=0.1\mu F$ ; unless otherwise specified.)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Output voltage	V <sub>out</sub>	T <sub>j</sub> =25°C		4.80	5	5.20	V
		7.5V≤V <sub>in</sub> ≤20V, 10mA≤I <sub>out</sub> ≤1.5A, PD≤15W		4.75	5	5.25	
Line Regulation	REGline	T <sub>j</sub> =25°C	7.5V≤V <sub>in</sub> ≤25V	--	3	100	mV
			8V≤V <sub>in</sub> ≤12V	--	1	50	
Load Regulation	REGload	T <sub>j</sub> =25°C	10mA≤I <sub>out</sub> ≤1.5A	--	15	100	mV
			250mA≤I <sub>out</sub> ≤750mA	--	5	50	
Quiescent Current	I <sub>q</sub>	I <sub>out</sub> =0, T <sub>j</sub> =25°C		--	4.2	8	mA
Quiescent Current Change	ΔI <sub>q</sub>	7.5V≤V <sub>in</sub> ≤25V		--	--	1.3	
		10mA≤I <sub>out</sub> ≤1.5A		--	--	0.5	
Output Noise Voltage	V <sub>n</sub>	10Hz≤f≤100KHz, T <sub>j</sub> =25°C		--	40	--	μV
Ripple Rejection Ratio	RR	f=120Hz, 8V≤V <sub>in</sub> ≤18V		62	78	--	dB
Voltage Drop	V <sub>drop</sub>	I <sub>out</sub> =1.0A, T <sub>j</sub> =25°C		--	2	--	V
Output Resistance	R <sub>out</sub>	f=1KHz		--	17	--	mΩ
Output Short Circuit Current	I <sub>os</sub>	T <sub>j</sub> =25°C		--	750	--	mA
Peak Output Current	I <sub>o peak</sub>	T <sub>j</sub> =25°C		--	2.2	--	A
Temperature Coefficient of Output Voltage	ΔV <sub>out</sub> / ΔT <sub>j</sub>	I <sub>out</sub> =10mA, 0°C≤T <sub>j</sub> ≤125°C		--	-0.6	--	mV/ °C

### TS7806B Electrical Characteristics

( $V_{in}=11V$ ,  $I_{out}=500mA$ ,  $0^{\circ}C \leq T_j \leq 125^{\circ}C$ ,  $C_{in}=0.33\mu F$ ,  $C_{out}=0.1\mu F$ ; unless otherwise specified.)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Output Voltage	V <sub>out</sub>	T <sub>j</sub> =25°C		5.75	6	6.25	V
		8.5V≤V <sub>in</sub> ≤21V, 10mA≤I <sub>out</sub> ≤1.5A, PD≤15W		5.7	6	6.3	
Line Regulation	REGline	T <sub>j</sub> =25°C	8.5V≤V <sub>in</sub> ≤25V	--	5	120	mV
			9V≤V <sub>in</sub> ≤13V	--	1.5	60	
Load Regulation	REGload	T <sub>j</sub> =25°C	10mA≤I <sub>out</sub> ≤1.5A	--	14	120	mV
			250mA≤I <sub>out</sub> ≤750mA	--	4	60	
Quiescent Current	I <sub>q</sub>	I <sub>out</sub> =0, T <sub>j</sub> =25°C		--	4.3	8	mA
Quiescent Current Change	ΔI <sub>q</sub>	8.5V≤V <sub>in</sub> ≤25V		--	--	1.3	
		10mA≤I <sub>out</sub> ≤1.5A		--	--	0.5	
Output Noise Voltage	V <sub>n</sub>	10Hz≤f≤100KHz, T <sub>j</sub> =25°C		--	45	--	uV
Ripple Rejection Ratio	RR	f=120Hz, 9V≤V <sub>in</sub> ≤19V		59	75	--	dB
Voltage Drop	V <sub>drop</sub>	I <sub>out</sub> =1.0A, T <sub>j</sub> =25°C		--	2	--	V
Output Resistance	R <sub>out</sub>	f=1KHz		--	19	--	mΩ
Output Short Circuit Current	I <sub>os</sub>	T <sub>j</sub> =25°C		--	550	--	mA
Peak Output Current	I <sub>o peak</sub>	T <sub>j</sub> =25°C		--	2.2	--	A
Temperature Coefficient of Output Voltage	ΔV <sub>out</sub> / ΔT <sub>j</sub>	I <sub>out</sub> =10mA, 0°C≤T <sub>j</sub> ≤125°C		--	-0.7	--	mV/ °C

- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.

### TS7808B Electrical Characteristics

( $V_{in}=14V$ ,  $I_{out}=500mA$ ,  $0^{\circ}C \leq T_j \leq 125^{\circ}C$ ,  $C_{in}=0.33\mu F$ ,  $C_{out}=0.1\mu F$ ; unless otherwise specified.)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Output voltage	$V_{out}$	$T_j=25^{\circ}C$		7.69	8	8.32	V
		$10.5V \leq V_{in} \leq 23V$ , $10mA \leq I_{out} \leq 1.5A$ , $PD \leq 15W$		7.61	8	8.40	
Line Regulation	REGline	$T_j=25^{\circ}C$	$10.5V \leq V_{in} \leq 25V$	--	6	160	mV
			$11V \leq V_{in} \leq 17V$	--	2	80	
Load Regulation	REGload	$T_j=25^{\circ}C$	$10mA \leq I_{out} \leq 1.5A$	--	12	160	mV
			$250mA \leq I_{out} \leq 750mA$	--	4	80	
Quiescent Current	$I_q$	$I_{out}=0$ , $T_j=25^{\circ}C$		--	4.3	8	mA
Quiescent Current Change	$\Delta I_q$	$10.5V \leq V_{in} \leq 25V$		--	--	1	
		$10mA \leq I_{out} \leq 1.5A$		--	--	0.5	
Output Noise Voltage	$V_n$	$10Hz \leq f \leq 100KHz$ , $T_j=25^{\circ}C$		--	52	--	$\mu V$
Ripple Rejection Ratio	RR	$f=120Hz$ , $11V \leq V_{in} \leq 21V$		56	72	--	dB
Voltage Drop	$V_{drop}$	$I_{out}=1.0A$ , $T_j=25^{\circ}C$		--	2	--	V
Output Resistance	$R_{out}$	$f=1KHz$		--	16	--	$m\Omega$
Output Short Circuit Current	$I_{os}$	$T_j=25^{\circ}C$		--	450	--	mA
Peak Output Current	$I_{o peak}$	$T_j=25^{\circ}C$		--	2.2	--	A
Temperature Coefficient of Output Voltage	$\Delta V_{out}/ \Delta T_j$	$I_{out}=10mA$ , $0^{\circ}C \leq T_j \leq 125^{\circ}C$		--	-0.8	--	$mV/ ^{\circ}C$

### TS7809B Electrical Characteristics

( $V_{in}=15V$ ,  $I_{out}=500mA$ ,  $0^{\circ}C \leq T_j \leq 125^{\circ}C$ ,  $C_{in}=0.33\mu F$ ,  $C_{out}=0.1\mu F$ ; unless otherwise specified.)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Output Voltage	$V_{out}$	$T_j=25^{\circ}C$		8.65	9	9.36	V
		$11.5V \leq V_{in} \leq 23V$ , $10mA \leq I_{out} \leq 1.5A$ , $PD \leq 15W$		8.57	9	9.45	
Line Regulation	REGline	$T_j=25^{\circ}C$	$11.5V \leq V_{in} \leq 26V$	--	6	180	mV
			$12V \leq V_{in} \leq 17V$	--	2	90	
Load Regulation	REGload	$T_j=25^{\circ}C$	$10mA \leq I_{out} \leq 1.5A$	--	12	180	mV
			$250mA \leq I_{out} \leq 750mA$	--	4	90	
Quiescent Current	$I_q$	$I_{out}=0$ , $T_j=25^{\circ}C$		--	4.3	8	mA
Quiescent Current Change	$\Delta I_q$	$11.5V \leq V_{in} \leq 26V$		--	--	1	
		$10mA \leq I_{out} \leq 1.5A$		--	--	0.5	
Output Noise Voltage	$V_n$	$10Hz \leq f \leq 100KHz$ , $T_j=25^{\circ}C$		--	52	--	$\mu V$
Ripple Rejection Ratio	RR	$f=120Hz$ , $12V \leq V_{in} \leq 22V$		55	72	--	dB
Voltage Drop	$V_{drop}$	$I_{out}=1.0A$ , $T_j=25^{\circ}C$		--	2	--	V
Output Resistance	$R_{out}$	$f=1KHz$		--	16	--	$m\Omega$
Output Short Circuit Current	$I_{os}$	$T_j=25^{\circ}C$		--	450	--	mA
Peak Output Current	$I_{o peak}$	$T_j=25^{\circ}C$		--	2.2	--	A
Temperature Coefficient of Output Voltage	$\Delta V_{out}/ \Delta T_j$	$I_{out}=10mA$ , $0^{\circ}C \leq T_j \leq 125^{\circ}C$		--	-1	--	$mV/ ^{\circ}C$

- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.

**TS7810B Electrical Characteristics**

( $V_{in}=16V$ ,  $I_{out}=500mA$ ,  $0^{\circ}C \leq T_j \leq 125^{\circ}C$ ,  $C_{in}=0.33\mu F$ ,  $C_{out}=0.1\mu F$ ; unless otherwise specified.)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Output voltage	$V_{out}$	$T_j=25^{\circ}C$		9.6	10	10.4	V
		$12.5V \leq V_{in} \leq 25V$ , $10mA \leq I_{out} \leq 1.5A$ , $PD \leq 15W$		9.5	10	10.5	
Line Regulation	REGline	$T_j=25^{\circ}C$	$12.5V \leq V_{in} \leq 28V$	--	7	200	mV
			$13V \leq V_{in} \leq 17V$	--	2	100	
Load Regulation	REGload	$T_j=25^{\circ}C$	$10mA \leq I_{out} \leq 1.5A$	--	12	200	
			$250mA \leq I_{out} \leq 750mA$	--	4	100	
Quiescent Current	$I_q$	$I_{out}=0$ , $T_j=25^{\circ}C$		--	4.3	8	mA
Quiescent Current Change	$\Delta I_q$	$12.5V \leq V_{in} \leq 28V$		--	--	1	
		$10mA \leq I_{out} \leq 1.5A$		--	--	0.5	
Output Noise Voltage	$V_n$	$10Hz \leq f \leq 100KHz$ , $T_j=25^{\circ}C$		--	70	--	$\mu V$
Ripple Rejection Ratio	RR	$f=120Hz$ , $13V \leq V_{in} \leq 23V$		55	71	--	dB
Voltage Drop	$V_{drop}$	$I_{out}=1.0A$ , $T_j=25^{\circ}C$		--	2	--	V
Output Resistance	$R_{out}$	$f=1KHz$		--	18	--	$m\Omega$
Output Short Circuit Current	$I_{os}$	$T_j=25^{\circ}C$		--	400	--	mA
Peak Output Current	$I_{o peak}$	$T_j=25^{\circ}C$		--	2.2	--	A
Temperature Coefficient of Output Voltage	$\Delta V_{out}/ \Delta T_j$	$I_{out}=10mA$ , $0^{\circ}C \leq T_j \leq 125^{\circ}C$		--	-1	--	$mV/ ^{\circ}C$

**TS7812B Electrical Characteristics**

( $V_{in}=19V$ ,  $I_{out}=500mA$ ,  $0^{\circ}C \leq T_j \leq 125^{\circ}C$ ,  $C_{in}=0.33\mu F$ ,  $C_{out}=0.1\mu F$ ; unless otherwise specified.)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Output Voltage	$V_{out}$	$T_j=25^{\circ}C$		11.53	12	12.48	V
		$14.5V \leq V_{in} \leq 27V$ , $10mA \leq I_{out} \leq 1.5A$ , $PD \leq 15W$		11.42	12	12.60	
Line Regulation	REGline	$T_j=25^{\circ}C$	$14.5V \leq V_{in} \leq 30V$	--	10	240	mV
			$15V \leq V_{in} \leq 19V$	--	3	120	
Load Regulation	REGload	$T_j=25^{\circ}C$	$10mA \leq I_{out} \leq 1.5A$	--	12	240	
			$250mA \leq I_{out} \leq 750mA$	--	4	120	
Quiescent Current	$I_q$	$T_j=25^{\circ}C$ , $I_{out}=0$		--	4.3	8	mA
Quiescent Current Change	$\Delta I_q$	$14.5V \leq V_{in} \leq 30V$		--	--	1	
		$10mA \leq I_{out} \leq 1.5A$		--	--	0.5	
Output Noise Voltage	$V_n$	$10Hz \leq f \leq 100KHz$ , $T_j=25^{\circ}C$		--	75	--	$\mu V$
Ripple Rejection Ratio	RR	$f=120Hz$ , $15V \leq V_{in} \leq 25V$		55	71	--	dB
Voltage Drop	$V_{drop}$	$I_{out}=1.0A$ , $T_j=25^{\circ}C$		--	2	--	V
Output Resistance	$R_{out}$	$f=1KHz$		--	18	--	$m\Omega$
Output Short Circuit Current	$I_{os}$	$T_j=25^{\circ}C$		--	350	--	mA
Peak Output Current	$I_{o peak}$	$T_j=25^{\circ}C$		--	2.2	--	A
Temperature Coefficient of Output Voltage	$\Delta V_{out}/ \Delta T_j$	$I_{out}=10mA$ , $0^{\circ}C \leq T_j \leq 125^{\circ}C$		--	-1	--	$mV/ ^{\circ}C$

- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.

### TS7815B Electrical Characteristics

( $V_{in}=23V$ ,  $I_{out}=500mA$ ,  $0^{\circ}C \leq T_j \leq 125^{\circ}C$ ,  $C_{in}=0.33\mu F$ ,  $C_{out}=0.1\mu F$ ; unless otherwise specified.)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Output voltage	$V_{out}$	$T_j=25^{\circ}C$		14.42	15	15.60	V
		$17.5V \leq V_{in} \leq 30V$ , $10mA \leq I_{out} \leq 1.5A$ , $PD \leq 15W$		14.28	15	15.75	
Line Regulation	REGline	$T_j=25^{\circ}C$	$17.5V \leq V_{in} \leq 30V$	--	12	300	mV
			$18V \leq V_{in} \leq 22V$	--	3	150	
Load Regulation	REGload	$T_j=25^{\circ}C$	$10mA \leq I_{out} \leq 1.5A$	--	12	300	
			$250mA \leq I_{out} \leq 750mA$	--	4	150	
Quiescent Current	$I_q$	$T_j=25^{\circ}C$ , $I_{out}=0$		--	4.3	8	mA
Quiescent Current Change	$\Delta I_q$	$17.5V \leq V_{in} \leq 30V$		--	--	1	
		$10mA \leq I_{out} \leq 1.5A$		--	--	0.5	
Output Noise Voltage	$V_n$	$10Hz \leq f \leq 100KHz$ , $T_j=25^{\circ}C$		--	90	--	$\mu V$
Ripple Rejection Ratio	RR	$f=120Hz$ , $18V \leq V_{in} \leq 28V$		54	70	--	dB
Voltage Drop	$V_{drop}$	$I_{out}=1.0A$ , $T_j=25^{\circ}C$		--	2	--	V
Output Resistance	$R_{out}$	$f=1KHz$		--	19	--	$m\Omega$
Output Short Circuit Current	$I_{os}$	$T_j=25^{\circ}C$		--	230	--	mA
Peak Output Current	$I_{o peak}$	$T_j=25^{\circ}C$		--	2.2	--	A
Temperature Coefficient of Output Voltage	$\Delta V_{out}/ \Delta T_j$	$I_{out}=10mA$ , $0^{\circ}C \leq T_j \leq 125^{\circ}C$		--	-1	--	$mV/ ^{\circ}C$

### TS7818B Electrical Characteristics

( $V_{in}=24V$ ,  $I_{out}=500mA$ ,  $0^{\circ}C \leq T_j \leq 125^{\circ}C$ ,  $C_{in}=0.33\mu F$ ,  $C_{out}=0.1\mu F$ ; unless otherwise specified.)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Output Voltage	$V_{out}$	$T_j=25^{\circ}C$		17.30	18	18.72	V
		$21V \leq V_{in} \leq 33V$ , $10mA \leq I_{out} \leq 1.5A$ , $PD \leq 15W$		17.14	18	18.90	
Line Regulation	REGline	$T_j=25^{\circ}C$	$21V \leq V_{in} \leq 33V$	--	15	360	mV
			$22V \leq V_{in} \leq 26V$	--	5	180	
Load Regulation	REGload	$T_j=25^{\circ}C$	$10mA \leq I_{out} \leq 1.5A$	--	12	360	
			$250mA \leq I_{out} \leq 750mA$	--	4	180	
Quiescent Current	$I_q$	$T_j=25^{\circ}C$ , $I_{out}=0$		--	4.5	8	mA
Quiescent Current Change	$\Delta I_q$	$21V \leq V_{in} \leq 33V$		--	--	1	
		$10mA \leq I_{out} \leq 1.5A$		--	--	0.5	
Output Noise Voltage	$V_n$	$10Hz \leq f \leq 100KHz$ , $T_j=25^{\circ}C$		--	110	--	$\mu V$
Ripple Rejection Ratio	RR	$f=120Hz$ , $21V \leq V_{in} \leq 31V$		54	70	--	dB
Voltage Drop	$V_{drop}$	$I_{out}=1.0A$ , $T_j=25^{\circ}C$		--	2	--	V
Output Resistance	$R_{out}$	$f=1KHz$		--	22	--	$m\Omega$
Output Short Circuit Current	$I_{os}$	$T_j=25^{\circ}C$		--	200	--	mA
Peak Output Current	$I_{o peak}$	$T_j=25^{\circ}C$		--	2.2	--	A
Temperature Coefficient of Output Voltage	$\Delta V_{out}/ \Delta T_j$	$I_{out}=10mA$ , $0^{\circ}C \leq T_j \leq 125^{\circ}C$		--	-1	--	$mV/ ^{\circ}C$

- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.


**TS7824B Electrical Characteristics**

Vin=33V, Iout=500mA, 0°C≤Tj≤125°C, Cin=0.33uF, Cout=0.1uF; unless otherwise specified.)


Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Output voltage	Vout	Tj=25°C		23.07	24	24.96	V
		27V≤Vin≤38V, 10mA≤Iout≤1.5A, PD ≤15W		22.85	24	25.20	
Line Regulation	REGline	Tj=25°C	27V≤Vin≤38V	--	18	480	mV
			28V≤Vin≤32V	--	6	240	
Load Regulation	REGload	Tj=25°C	10mA≤Iout≤1.5A	--	12	480	mV
			250mA≤Iout≤750mA	--	4	240	
Quiescent Current	Iq	Iout=0, Tj=25°C		--	4.6	8	mA
Quiescent Current Change	ΔIq	27V≤Vin≤38V		--	--	1	
		10mA≤Iout≤1.5A		--	--	0.5	
Output Noise Voltage	Vn	10Hz≤f≤100KHz, Tj=25°C		--	170	--	μV
Ripple Rejection Ratio	RR	f=120Hz, 27V≤Vin≤37V		54	70	--	dB
Voltage Drop	Vdrop	Iout=1.0A, Tj=25°C		--	2	--	V
Output Resistance	Rout	f=1KHz		--	28	--	mΩ
Output Short Circuit Current	Ios	Tj=25°C		--	150	--	mA
Peak Output Current	Io peak	Tj=25°C		--	2.2	--	A
Temperature Coefficient of Output Voltage	ΔVout/ ΔTj	Iout=10mA, 0°C≤Tj≤125°C		--	-1.5	--	mV/ °C

- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.


### Electrical Characteristics Curve




**Figure 1. Peak Output Current as a Function of Input-Output Differential Voltage**




**Figure 2. Ripple Rejection as a Function of Output Voltage**




**Figure 3. Ripple Rejection as a Function of Frequency**




**Figure 4. Output Voltage as a Function of Junction Temperature**



**Figure 5. Output Impedance as a Function of Output Voltage**




**Figure 6. Quiescent Current as a Function of Temperature**

**Application Information**


**Figure 7. D<sup>2</sup>PAK Thermal Resistance and Maximum Power Dissipation vs. P.C.B Copper Length**

### TO-220 Mechanical Drawing




DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	10.000	10.500	0.394	0.413
B	3.740	3.910	0.147	0.154
C	2.440	2.940	0.096	0.116
D	-	6.350	-	0.250
E	0.381	1.106	0.015	0.040
F	2.345	2.715	0.092	0.058
G	4.690	5.430	0.092	0.107
H	12.700	14.732	0.500	0.581
I	8.382	9.017	0.330	0.355
J	14.224	16.510	0.560	0.650
K	3.556	4.826	0.140	0.190
L	0.508	1.397	0.020	0.055
M	27.700	29.620	1.060	1.230
N	2.032	2.921	0.080	0.115
O	0.255	0.610	0.010	0.024
P	5.842	6.858	0.230	0.270

### Marking Diagram




- XX** = Output Voltage  
(05=5V, 06=6V, 08=8V, 09=9V, 10=10V, 12=12V, 15=15V, 18=18V, 24=24V)
- Y** = Year Code
- M** = Month Code  
(A=Jan, B=Feb, C=Mar, D=Apl, E=May, F=Jun, G=Jul, H=Aug, I=Sep, J=Oct, K=Nov, L=Dec)
- L** = Lot Code
- CZ** = Package Code for TO-220

### ITO-220 Mechanical Drawing




DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	9.96	10.36	0.392	0.407
B	6.20 (typ.)		0.244 (typ.)	
C	2.20 (typ.)		0.087 (typ.)	
D	§ 1.40 (typ.)		§ 0.055 (typ.)	
E	15.07	16.07	0.593	0.632
F	0.80 (typ.)		0.031 (typ.)	
G	2.44	2.64	0.096	0.104
H	13.08	13.48	0.514	0.530
I	1.47 (max.)		0.057 (max.)	
J	3.20	3.40	0.125	0.133
K	4.60	4.80	0.181	0.188
L	1.15 (typ.)		0.045 (typ.)	
M	2.44	2.64	0.096	0.104
N	2.60	2.80	0.102	0.110
O	6.55	6.65	0.258	0.262

### Marking Diagram



- XX** = Output Voltage  
(05=5V, 06=6V, 08=8V, 09=9V, 10=10V, 12=12V, 15=15V, 18=18V, 24=24V)
- Y** = Year Code
- M** = Month Code  
(A=Jan, B=Feb, C=Mar, D=Apl, E=May, F=Jun, G=Jul, H=Aug, I=Sep,  
J=Oct, K=Nov, L=Dec)
- L** = Lot Code
- CI** = Package Code for ITO-220

### TO-263 Mechanical Drawing



TO-263 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	10.000	10.500	0.394	0.413
B	14.605	15.875	0.575	0.625
C	0.508	0.991	0.020	0.039
D	2.420	2.660	0.095	0.105
E	4.064	4.830	0.160	0.190
F	1.118	1.400	0.045	0.055
G	0.450	0.730	0.018	0.029
H	8.280	8.800	0.325	0.346
I	1.140	1.400	0.044	0.055
J	1.480	1.520	0.058	0.060

### Marking Diagram



- XX** = Output Voltage  
(05=5V, 06=6V, 08=8V, 09=9V, 10=10V, 12=12V, 15=15V, 18=18V, 24=24V)
- Y** = Year Code
- M** = Month Code  
(A=Jan, B=Feb, C=Mar, D=Apl, E=May, F=Jun, G=Jul, H=Aug, I=Sep,  
J=Oct, K=Nov, L=Dec)
- L** = Lot Code
- CM** = Package Code for TO-263

## Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.