

# BRIGHT LED ELECTRONICS

- Device Number: BPI-3C1-18
- Absolute Maximum Rating (Ta=25°C)

Page: 2  
Version: 1.2

Item		Symbol	Rating	Unit
Input	Power Dissipation	Pd	75	mW
	Reverse Voltage	V <sub>R</sub>	6	V
	Forward Current	I <sub>F</sub>	50	mA
	Peak Forward Current (*1)	I <sub>FP</sub>	1	A
Output	Collector Power Dissipation	P <sub>C</sub>	75	mW
	Collector Current	I <sub>C</sub>	20	mA
	C-E Voltage	V <sub>CEO</sub>	35	V
	E-C Voltage	V <sub>ECO</sub>	6	V
Operating Temperature		Topr	-25 ~ +85	°C
Storage Temperature		Tstg	-40 ~ +85	°C
Soldering Temperature (*2)		Tsol	260	°C

(\*1) tw=100 uSec, T=10 mSec.

(\*2) t=5 Sec




- Electrical Optical Characteristics (Ta=25°C)

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit
Input	Forward Voltage	V <sub>F</sub>	I <sub>F</sub> =20mA	---	1.25	1.4	V
	Reverse Current	I <sub>R</sub>	V <sub>R</sub> =5V	---	---	10	μA
	Peak Wavelength	λ <sub>p</sub>	I <sub>F</sub> =10mA	---	940	---	nm
Output	Dark Current	I <sub>D</sub>	V <sub>CE</sub> =10V	---	1	100	nA
	C-E Saturation Voltage	V <sub>CE(sat)</sub>	I <sub>C</sub> =0.25mA I <sub>F</sub> =10mA	---	---	0.4	V
Light Current		I <sub>L</sub>	V <sub>CE</sub> =5V I <sub>F</sub> =20mA	1.0	---	10	mA
Speed	Rise Time	Tr	I <sub>C</sub> =2mA V <sub>CE</sub> =5V	---	15	---	μsec
	Fall Time	Tf	R <sub>L</sub> =1000Ω	---	15	---	μsec

# BRIGHT LED ELECTRONICS

● Device Number: BPI-3C1-18  
 ● Package Dimensions

Page: 3  
 Version: 1.2



## Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is  $\pm 0.20$ mm unless otherwise specified.
3. Lead spacing is measured where the leads emerge from the package.
4. Specifications are subject to change without notice.

# BRIGHT LED ELECTRONICS

● Device Number: BPI-3C1-18  
 ● Typical Electrical / Optical Characteristics Curves (Ta=25°C)

Page: 4  
 Version: 1.0

Fig.1 Power Dissipation vs. Ambient Temperature




Fig.2 Forward Current vs. Forward Voltage




Fig.3 Collector Current vs. Collector-emitter Voltage





Fig.4 Collector Current vs. Ambient Temperature



# BRIGHT LED ELECTRONICS

- Device Number: BPI-3C1-18
- Typical Electric / Optical Characteristics Curves ( $T_a=25^\circ\text{C}$ )

Page: 5  
Version: 1.0

Fig.5 Collector-emitter Saturation Voltage vs. Ambient Temperature




Fig.6 Response Time vs. Load Resistance







Fig.7 Sensing Position Characteristics (Typical)



(Center of Optical axis)




Test Circuit for Response Time




# BRIGHT LED ELECTRONICS

- Device Number: BPI-3C1-18
- Packaging Box Dimensions

Page: 6  
Revision: 1.0



- Packaging Bag Dimensions



## Notes:

1. 500pcs per bag, 2kpcs per box.
2. All Dimensions are in millimeters (inches).
3. Specifications are subject to change without notice.