Vishay Draloric



Ceramic Stand-off Insulators for RF-Equipment



• Dimensions in millimeters (inches)

MODEL	DIMENSIONS H	CAPACITANCE VALUES [pF]	FLASHOVER VOLTAGE AT 50 Hz AND 60 % REL. AIR HUMIDITY [KV _{RMS}]	OPERATING VOLTAGE [KV _{RMS}]	DISSIPATION FACTOR
3540/6	40 (1.575)	2.5	25	10	≤ 0.5 • 10- ³ [1 MHz]
3550/6	50 (1.969)	1.9	29	12	
3558/6	58 (2.283)	1.2	33	13	
3560/6	60 (2.362)	1.2	33	13	
3570/6	70 (2.756)	0.9	37	15	
3580/6	80 (3.150)	0.7	41	16	
35100/6	100 (3.937)	0.5	48	19	
35125/6	125 (4.921)	0.3	56	22	

Thread holes M8 and M10 as well as thread-holes according to US standard are available on request.

.

MATERIAL:

Stand - off insulator elements made from Class 1 Ceramic material (C 221-IEC 60672-3), body completely glazed. Connection terminals: brass

MARKING:

None

OPERATING CONDITIONS:

Maximum operating temperature	+ 100 °C
Maximum compressive load	3.0 kN
Maximum tensile load	7.5 kN
Maximum reactive current	3 A _{RMS}

ORDERING INFORMATION

Stand-off insulator 35100 / 6



Vishay

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.