

Surface Mount, Multi Layer High Frequency Ceramic Inductor



MECHANICAL SPECIFICATIONS

Solderability: 90 % coverage after 5 s dip in 235 °C solder following 60 s preheat at 120 °C and type R flux dip

Resistance to Solder Heat: 10 s in 260 °C solder, after preheat and flux above

Terminal Strength: 0.3 kg (0.66 lbs) for 30 s

Beam Strength: 0.3 kg (0.66 lbs)

Flex: 0.0788" [2.0 mm] minimum mounted on 0.063" [1.6 mm] thick PC board

FEATURES

- High reliability
- Surface mountable
- Reflow or wave solderable
- Tape and reel packaging per EIA specifications: 4000 pieces on 7" reel
- 100 % lead (Pb)-free and RoHS compliant



**RoHS
COMPLIANT**

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature: - 55 °C to + 125 °C

Thermal Shock: 100 cycles, - 40 °C to + 85 °C


Humidity: + 40 °C, 85 % RH, 1000 hat full rated current

Load Life: 85 °C for 1000 h full rated current

STANDARD ELECTRICAL SPECIFICATIONS

PART NUMBER	INDUCTANCE (nH)	TOL.	Q (MIN.)	TEST FREQUENCY (MHz)	Q (TYPICAL)			DCR MAX. (Ω)	SRF (MHz)		MAX. RATED CURRENT (mA)
					100 MHz	500 MHz	1000 MHz		MIN.	TYP.	
ILC0603ER1N0S	1.0	± 0.3 nH	8	100	15	43	63	0.05	10 000	15 000	300
ILC0603ER1N2S	1.2	± 0.3 nH	8	100	14	38	55	0.05	10 000	14 000	300
ILC0603ER1N5S	1.5	± 0.3 nH	8	100	11	28	40	0.10	6000	13 000	300
ILC0603ER1N8S	1.8	± 0.3 nH	8	100	10	24	35	0.10	6000	11 000	300
ILC0603ER2N2S	2.2	± 0.3 nH	8	100	14	35	40	0.10	6000	10 000	300
ILC0603ER2N7S	2.7	± 0.3 nH	10	100	12	29	45	0.10	6000	7000	300
ILC0603ER3N3S	3.3	± 0.3 nH	10	100	16	40	47	0.12	4000	5900	300
ILC0603ER3N9S	3.9	± 0.3 nH	10	100	11	25	35	0.14	3500	4500	300
ILC0603ER4N7S	4.7	± 0.3 nH	10	100	11	26	35	0.16	3500	4500	300
ILC0603ER5N6S	5.6	± 0.3 nH	10	100	15	36	46	0.18	3500	4000	300
ILC0603ER6N8J	6.8	± 5 %	10	100	15	38	47	0.22	3000	3600	300
ILC0603ER8N2J	8.2	± 5 %	10	100	13	31	41	0.24	3000	3500	300
ILC0603ER10NJ	10	± 5 %	12	100	15	34	47	0.26	2800	3000	300
ILC0603ER12NJ	12	± 5 %	12	100	12	27	49	0.28	2000	2500	300
ILC0603ER15NJ	15	± 5 %	12	100	15	30	36	0.32	2000	2200	300
ILC0603ER18NJ	18	± 5 %	12	100	15	28	31	0.35	1800	2000	300
ILC0603ER22NJ	22	± 5 %	12	100	17	34	36	0.40	1800	1900	300
ILC0603ER27NJ	27	± 5 %	12	100	15	31	30	0.45	1500	1700	300
ILC0603ER33NJ	33	± 5 %	12	100	15	28	24	0.55	1200	1500	300
ILC0603ER39NJ	39	± 5 %	12	100	14	31	28	0.60	1100	1300	300
ILC0603ER47NJ	47	± 5 %	12	100	17	31	28	0.70	900	1300	300
ILC0603ER56NJ	56	± 5 %	12	100	19	34	26	0.75	900	1200	300
ILC0603ER68NJ	68	± 5 %	12	100	17	30	20	0.85	700	1000	300
ILC0603ER82NJ	82	± 5 %	12	100	16	29	18	0.95	600	1000	300
ILC0603ERR10J	100	± 5 %	12	100	16	24	3	1.00	600	800	300
ILC0603ERR12J	120	± 5 %	8	50	17	21	-	1.20	500	800	300
ILC0603ERR15J	150	± 5 %	8	50	19	20	-	1.20	500	700	300
ILC0603ERR18J	180	± 5 %	8	50	18	13	-	1.30	400	600	300
ILC0603ERR22J	220	± 5 %	8	50	18	-	-	1.50	400	500	300
ILC0603ERR27J	270	± 5 %	8	50	19	-	-	1.60	350	490	300

DIMENSIONS in inches [millimeters]



DESCRIPTION

ILC-0603 MODEL	10 nH INDUCTANCE VALUE	± 10 % INDUCTANCE TOLERANCE	ER PACKAGE CODE	e3 JEDEC LEAD (Pb)-FREE STANDARD
-------------------	------------------------------	-----------------------------------	-----------------------	--

GLOBAL PART NUMBER

I L C	0 6 0 3	E R	1 0 N	K
PRODUCT FAMILY	SIZE	PACKAGE CODE	INDUCTANCE VALUE	TOL.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.