


## Cool MOS™ Power Transistor

### Feature


- New revolutionary high voltage technology
- Worldwide best  $R_{DS(on)}$  in TO252
- Ultra low gate charge
- Periodic avalanche rated
- Extreme dv/dt rated
- Pb-free lead plating; RoHS compliant
- Qualified according to JEDEC<sup>0)</sup> for target applications

$V_{DS}$	800	V
$R_{DS(on)}$	0.9	$\Omega$
$I_D$	6	A

PG-T0252



Type	Package	Ordering Code	Marking
SPD06N80C3	PG-T0252	Q67040-S4352	06N80C3



### Maximum Ratings, at $T_C = 25^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Value	Unit
Continuous drain current $T_C = 25^\circ\text{C}$	$I_D$	6	A
$T_C = 100^\circ\text{C}$			
Pulsed drain current, $t_p$ limited by $T_{jmax}$	$I_{D \text{ puls}}$	18	
Avalanche energy, single pulse $I_D=1.2\text{A}, V_{DD}=50\text{V}$	$E_{AS}$	230	mJ
Avalanche energy, repetitive $t_{AR}$ limited by $T_{jmax}$ <sup>1)</sup> $I_D=6\text{A}, V_{DD}=50\text{V}$	$E_{AR}$	0.2	
Avalanche current, repetitive $t_{AR}$ limited by $T_{jmax}$	$I_{AR}$	6	A
Gate source voltage	$V_{GS}$	$\pm 20$	V
Power dissipation, $T_C = 25^\circ\text{C}$	$P_{tot}$	83	W
Operating and storage temperature	$T_j, T_{stg}$	-55... +150	°C

**Maximum Ratings**

Parameter	Symbol	Value	Unit
Drain Source voltage slope $V_{DS} = 640 \text{ V}, I_D = 6 \text{ A}, T_j = 125 \text{ }^\circ\text{C}$	$dv/dt$	50	V/ns

**Thermal Characteristics**

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
Thermal resistance, junction - case	$R_{thJC}$	-	-	1.5	K/W
Thermal resistance, junction - ambient, leaded	$R_{thJA}$	-	-	62	
SMD version, device on PCB: @ min. footprint @ 6 cm <sup>2</sup> cooling area <sup>2)</sup>	$R_{thJA}$	-	-	75	
-	-	-	-	50	
Soldering temperature, reflow soldering, MSL3 1.6 mm (0.063 in.) from case for 10s <sup>3)</sup>	$T_{sold}$	-	-	260	°C

**Electrical Characteristics**

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS}=0\text{V}, I_D=0.25\text{mA}$	800	-	-	V
Drain-Source avalanche breakdown voltage	$V_{(BR)DS}$	$V_{GS}=0\text{V}, I_D=6\text{A}$	-	870	-	
Gate threshold voltage	$V_{GS(th)}$	$I_D=250\mu\text{A}, V_{GS}=V_{DS}$	2.1	3	3.9	
Zero gate voltage drain current	$I_{DSS}$	$V_{DS}=800\text{V}, V_{GS}=0\text{V}, T_j=25\text{ }^\circ\text{C}, T_j=150\text{ }^\circ\text{C}$	-	0.5	10	$\mu\text{A}$
-	-	-	-	-	100	
Gate-source leakage current	$I_{GSS}$	$V_{GS}=20\text{V}, V_{DS}=0\text{V}$	-	-	100	
Drain-source on-state resistance	$R_{DS(on)}$	$V_{GS}=10\text{V}, I_D=3.8\text{A}, T_j=25\text{ }^\circ\text{C}, T_j=150\text{ }^\circ\text{C}$	-	0.78	0.9	
-	-	-	-	2.1	-	
Gate input resistance	$R_G$	f=1MHz, open Drain	-	0.7	-	

**Electrical Characteristics , at  $T_j = 25^\circ\text{C}$ , unless otherwise specified**

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Transconductance	$g_{fs}$	$V_{DS} \geq 2 * I_D * R_{DS(on)max}$ , $I_D = 3.8\text{A}$	-	4	-	S
Input capacitance	$C_{iss}$	$V_{GS} = 0\text{V}$ , $V_{DS} = 25\text{V}$ , $f = 1\text{MHz}$	-	785	-	pF
Output capacitance	$C_{oss}$		-	390	-	
Reverse transfer capacitance	$C_{rss}$		-	20	-	
Effective output capacitance, <sup>4)</sup> energy related	$C_{o(er)}$	$V_{GS} = 0\text{V}$ , $V_{DS} = 0\text{V to } 480\text{V}$	-	22	-	pF
Effective output capacitance, <sup>5)</sup> time related	$C_{o(tr)}$		-	42	-	
Turn-on delay time	$t_{d(on)}$	$V_{DD} = 400\text{V}$ , $V_{GS} = 0/10\text{V}$ , $I_D = 6\text{A}$ , $R_G = 15\Omega$ , $T_j = 125^\circ\text{C}$	-	25	-	ns
Rise time	$t_r$		-	15	-	
Turn-off delay time	$t_{d(off)}$		-	65	75	
Fall time	$t_f$		-	8	11	

**Gate Charge Characteristics**

Gate to source charge	$Q_{gs}$	$V_{DD} = 640\text{V}$ , $I_D = 6\text{A}$	-	3.3	-	nC
Gate to drain charge	$Q_{gd}$		-	14	-	
Gate charge total	$Q_g$	$V_{DD} = 640\text{V}$ , $I_D = 6\text{A}$ , $V_{GS} = 0$ to $10\text{V}$	-	27	35	
Gate plateau voltage	$V_{(plateau)}$	$V_{DD} = 640\text{V}$ , $I_D = 6\text{A}$	-	6	-	V

<sup>0</sup>J-STD20 and JESD22

<sup>1</sup>Repetitive avalanche causes additional power losses that can be calculated as  $P_{AV} = E_{AR} * f$ .

<sup>2</sup>Device on 40mm\*40mm\*1.5mm epoxy PCB FR4 with 6cm<sup>2</sup> (one layer, 70 µm thick) copper area for drain connection. PCB is vertical without blown air.

<sup>3</sup>Soldering temperature for TO-263: 220°C, reflow

<sup>4</sup> $C_{o(er)}$  is a fixed capacitance that gives the same stored energy as  $C_{oss}$  while  $V_{DS}$  is rising from 0 to 80%  $V_{DSS}$ .


<sup>5</sup> $C_{o(tr)}$  is a fixed capacitance that gives the same charging time as  $C_{oss}$  while  $V_{DS}$  is rising from 0 to 80%  $V_{DSS}$ .

**Electrical Characteristics**, at  $T_j = 25^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Inverse diode continuous forward current	$I_S$	$T_C=25^\circ\text{C}$	-	-	6	A
Inverse diode direct current, pulsed	$I_{SM}$		-	-	18	
Inverse diode forward voltage	$V_{SD}$	$V_{GS}=0\text{V}$ , $I_F=I_S$	-	1	1.2	V
Reverse recovery time	$t_{rr}$	$V_R=400\text{V}$ , $I_F=I_S$ , $dI_F/dt=100\text{A}/\mu\text{s}$	-	520	-	ns
Reverse recovery charge	$Q_{rr}$		-	5	-	$\mu\text{C}$
Peak reverse recovery current	$I_{rrm}$		-	18	-	A
Peak rate of fall of reverse recovery current	$dI_{rr}/dt$		-	400	-	$\text{A}/\mu\text{s}$


**Typical Transient Thermal Characteristics**

Symbol	Value	Unit	Symbol	Value	Unit
Thermal resistance			Thermal capacitance		
$R_{th1}$	0.024	K/W	$C_{th1}$	0.0001172	Ws/K
$R_{th2}$	0.024		$C_{th2}$	0.000447	
$R_{th3}$	0.086		$C_{th3}$	0.0006303	
$R_{th4}$	0.309		$C_{th4}$	0.001828	
$R_{th5}$	0.317		$C_{th5}$	0.004786	
$R_{th6}$	0.112		$C_{th6}$	0.046	



## 1 Power dissipation


$$P_{\text{tot}} = f(T_C)$$



## 2 Safe operating area

$$I_D = f(V_{DS})$$


parameter :  $D = 0$ ,  $T_C = 25^\circ\text{C}$



## 3 Transient thermal impedance

$$Z_{\text{thJC}} = f(t_p)$$


parameter:  $D = t_p/T$



## 4 Typ. output characteristic


$$I_D = f(V_{DS}); \quad T_j = 25^\circ\text{C}$$

parameter:  $t_p = 10 \mu\text{s}$ ,  $V_{GS}$




### 5 Typ. output characteristic

$I_D = f(V_{DS})$ ;  $T_j=150^\circ\text{C}$   
parameter:  $t_p = 10 \mu\text{s}$ ,  $V_{GS}$




### 6 Typ. drain-source on resistance

$R_{DS(on)}=f(I_D)$   
parameter:  $T_j=150^\circ\text{C}$ ,  $V_{GS}$




### 7 Drain-source on-state resistance

$R_{DS(on)} = f(T_j)$   
parameter :  $I_D = 3.8 \text{ A}$ ,  $V_{GS} = 10 \text{ V}$



### 8 Typ. transfer characteristics


$I_D = f( V_{GS} )$ ;  $V_{DS} \geq 2 \times I_D \times R_{DS(on)\max}$   
parameter:  $t_p = 10 \mu\text{s}$



### 9 Typ. gate charge

$$V_{GS} = f(Q_{Gate})$$


parameter:  $I_D = 6 \text{ A pulsed}$



### 11 Avalanche SOA

$$I_{AR} = f(t_{AR})$$


par.:  $T_j \leq 150^\circ\text{C}$



### 10 Forward characteristics of body diode

$$I_F = f(V_{SD})$$


parameter:  $T_j, t_p = 10 \mu\text{s}$



### 12 Avalanche energy


$$E_{AS} = f(T_j)$$

par.:  $I_D = 1.2 \text{ A}, V_{DD} = 50 \text{ V}$



### 13 Drain-source breakdown voltage


$$V_{(BR)DSS} = f(T_j)$$



### 14 Avalanche power losses

$$P_{AR} = f(f)$$


parameter:  $E_{AR}=0.2\text{mJ}$



### 15 Typ. capacitances


$$C = f(V_{DS})$$

parameter:  $V_{GS}=0\text{V}$ ,  $f=1\text{ MHz}$




### 16 Typ. $C_{OSS}$ stored energy


$$E_{OSS}=f(V_{DS})$$



### Definition of diodes switching characteristics



PG-T0252-3-1, PG-T0252-3-11, PG-T0252-3-21 (D-PAK)



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.16	2.41	0.085	0.095
A1	0.00	0.15	0.000	0.006
b	0.64	0.89	0.025	0.035
b2	0.65	1.15	0.026	0.045
b3	5.00	5.50	0.197	0.217
c	0.46	0.60	0.018	0.024
c2	0.46	0.98	0.018	0.039
D	5.97	6.22	0.235	0.245
D1	5.02	5.84	0.198	0.230
E	6.40	6.73	0.252	0.265
E1	4.70	5.21	0.185	0.205
e	2.29		0.090	
e1	4.57		0.180	
N	3		3	
H	9.40	10.48	0.370	0.413
L	1.18	1.70	0.046	0.067
L3	0.90	1.25	0.035	0.049
L4	0.51	1.00	0.020	0.039
F1	10.50	10.70	0.413	0.421
F2	6.30	6.50	0.248	0.256
F3	2.10	2.30	0.083	0.091
F4	5.70	5.90	0.224	0.232
F5	5.66	5.86	0.223	0.231
F6	1.10	1.30	0.043	0.051

DOCUMENT NO.	
Z8B00003328	
SCALE	0 2.0 0 2.0
4mm	
EUROPEAN PROJECTION	
ISSUE DATE 19-10-2007	
REVISION 03	

---

**Published by**  
**Infineon Technologies AG**  
**81726 Munich, Germany**  
**© 2008 Infineon Technologies AG**  
**All Rights Reserved.**

#### **Legal Disclaimer**

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

#### **Information**

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office ([www.infineon.com](http://www.infineon.com)).

#### **Warnings**

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.