


SZ3C 1 ... SZ3C 200 (3W)



Surface mount diode

Zener silicon diodes

SZ3C 1...SZ3C 200 (3W)

Maximum Power Dissipation: 3 W

Nominal Z-voltage: 1 to 200 V

Features

- Max. solder temperature: 260°C
- Plastic material has UL classification 94V-0
- Standard Zener voltage tolerance is graded to the international E 24 (5%) standard. Other voltage tolerances and higher Zener voltages on request.

Mechanical Data

- Plastic case Melf / DO-213AB
- Weight approx.: 0,12 g
- Terminals: plated terminals solderable per MIL-STD-750
- Mounting position: any
- Standard packaging: 5000 pieces per reel

1) Mounted on P.C. board with 50 mm² copper pads at each terminal

2) Tested with pulses

3) The SZ3C1 is a diode operated in forward. Hence, the index of all parameters should be "F" instead of "Z". The cathode, indicated by a white ring is to be connected to the negative pole.

Absolute Maximum Ratings		$T_c = 25\text{ }^\circ\text{C}$, unless otherwise specified	
Symbol	Conditions	Values	Units
P_{tot}	Power dissipation, $T_A = 50\text{ }^\circ\text{C}$ ¹⁾	3	W
P_{ZSM}	Non repetitive peak power dissipation, $t < 10\text{ ms}$	60	W
R_{thA}	Max. thermal resistance junction to ambient	33	K/W
R_{thT}	Max. thermal resistance junction to terminal	10	K/W
T_j	Operating junction temperature	- 50 ... + 150	°C
T_s	Storage temperature	- 50 ... + 175	°C

Type	Zener Voltage ²⁾ $V_Z@I_{ZT}$		Test curr. I_{ZT} mA	Dyn. Resistance $Z_{ZT}@I_{ZT}$ Ω	Temp. Coeffiz. of V_Z a_{VZ} $10^{-4}/^\circ\text{C}$			Z-curr. ¹⁾ $T_A = 50\text{ }^\circ\text{C}$ $I_{Z\text{max}}$ mA
	$V_{Z\text{min}}$ V	$V_{Z\text{max}}$ V				I_R μA	V_R V	
SZ3C 1 ³⁾	0,71	0,82	100	0,5 (<1)	- 26 ... - 16		-	2000
SZ3C 10	9,4	10,6	50	2 (<4)	+ 5 ... + 9	1	> 5	283
SZ3C 11	10,4	11,6	50	4 (<7)	+ 5 ... + 10	1	> 5	259
SZ3C 12	11,4	12,7	50	4 (<7)	+ 5 ... + 10	1	> 7	236
SZ3C 13	12,4	14,1	50	5 (<10)	+ 5 ... + 10	1	> 7	213
SZ3C 15	13,8	15,6	50	5 (<10)	+ 5 ... + 10	1	> 10	192
SZ3C 16	15,3	17,1	25	6 (<15)	+ 6 ... + 11	1	> 10	175
SZ3C 18	16,8	19,1	25	6 (<15)	+ 6 ... + 11	1	> 10	157
SZ3C 20	18,8	21,2	25	6 (<15)	+ 6 ... + 11	1	> 10	142
SZ3C 22	20,8	23,3	25	6 (<15)	+ 6 ... + 11	1	> 12	129
SZ3C 24	22,8	25,6	25	7 (<15)	+ 6 ... + 11	1	> 12	117
SZ3C 27	25,1	28,9	25	7 (<15)	+ 6 ... + 11	1	> 14	104
SZ3C 30	28	32	25	8 (<15)	+ 6 ... + 11	1	> 14	94
SZ3C 33	31	35	25	8 (<15)	+ 6 ... + 11	1	> 17	86
SZ3C 36	34	38	10	16 (<30)	+ 6 ... + 11	1	> 17	79
SZ3C 39	37	41	10	20 (<40)	+ 6 ... + 11	1	> 20	73
SZ3C 43	40	46	10	24 (<40)	+ 7 ... + 12	1	> 20	65
SZ3C 47	44	50	10	24 (<40)	+ 7 ... + 12	1	> 24	60
SZ3C 51	48	54	10	25 (<60)	+ 7 ... + 12	1	> 24	56
SZ3C 56	52	60	10	25 (<60)	+ 7 ... + 12	1	> 28	50
SZ3C 62	58	66	10	25 (<80)	+ 8 ... + 13	1	> 28	45
SZ3C 68	64	72	10	25 (<80)	+ 8 ... + 13	1	> 34	42
SZ3C 75	70	79	10	30 (<100)	+ 8 ... + 13	1	> 34	38
SZ3C 82	77	88	10	30 (<100)	+ 8 ... + 13	1	> 41	34
SZ3C 91	85	96	5	40 (<150)	+ 9 ... + 13	1	> 41	31
SZ3C 100	94	106	5	60 (<150)	+ 9 ... + 13	1	> 50	28
SZ3C 110	104	116	5	80 (<200)	+ 9 ... + 13	1	> 50	26
SZ3C 120	114	127	5	80 (<200)	+ 9 ... + 13	1	> 60	24
SZ3C 130	124	141	5	90 (<250)	+ 9 ... + 13	1	> 60	21
SZ3C 150	138	156	5	100 (<250)	+ 9 ... + 13	1	> 75	19
SZ3C 160	153	171	5	110 (<300)	+ 9 ... + 13	1	> 75	18
SZ3C 180	168	191	5	120 (<350)	+ 9 ... + 13	1	> 90	16
SZ3C 200	188	212	5	150 (<350)	+ 9 ... + 13	1	> 90	14