


HCMOS 4 pad SMD, 'V' Group

- Miniature 11.4 x 9.6 x 2.5mm SMD package
- Wide frequency range: 27.0MHz to 200.0MHz
- Supply voltage 3.3 Volts
- Frequency stability from ± 1 ppm over -30 to $+75^\circ\text{C}$
- RoHS compliant



DESCRIPTION

EMV42GT series TCXOs are packaged in a miniature 4 pad ceramic SMD package. With squarewave (CMOS) output, tolerances are available from ± 1.0 ppm over -30° to $+75^\circ\text{C}$. The part has a 0.01 μF decoupling capacitor built in.

SPECIFICATION


Product Series Code	TCXO:	EMV42GT
	VCTCXO:	VEMV42GT
Frequency Range:	27.0MHz to 200.0MHz	
Output Waveform:	Squarewave, HCMOS	
Initial Calibration Tolerance		
	Models without trimmer:	$< \pm 2.0$ ppm
	Models with trimmer:	$< \pm 1.0$ ppm
Standard Frequencies:	30.0, 32.768, 38.880, 40.0, 50.0, 54.0, 64.0, 65.536, 77.76, 80.0, 128.0, 160.0 and 200.0MHz (Partial list)	
Operating Temperature Range:	See table	
Mechanical Frequency Tuning:	± 3.0 ppm minimum	
Frequency Stability		
	vs. Ageing:	± 1.0 ppm max. first year
	vs. Voltage Change:	± 0.3 ppm max. $\pm 5\%$ change
	vs. Load Change:	± 0.3 ppm max. $\pm 10\%$ change
	vs. Reflow (SMD type):	± 1.0 ppm max. for one reflow (Measured after 24 hours)
Supply Voltage:	+3.3 Volts	
Output Logic Levels:	Logic High: 90% Vdd min. Logic Low: 10% Vdd max.	
Current Consumption:	40mA maximum	
Rise and Fall Times:	10ns typical	
Duty Cycle:	50% $\pm 10\%$ standard,	
Start-up Time:	5ms typical, 10ms max.	
Current Consumption:	See table below	
Output Load:	15pF	
Storage Temperature:	$-55 \sim +125^\circ\text{C}$	

FREQUENCY STABILITY

Stability (ppm)		± 0.5	± 1.0	± 1.5	± 2.0	± 2.5	± 3.0
Temp. Range ($^\circ\text{C}$)	0 ~ +50	✓	✓	✓	✓	✓	✓
	-10 ~ +60	ASK	✓	✓	✓	✓	✓
	-20 ~ +70	X	✓	✓	✓	✓	✓
	-30 ~ +75	X	✓	✓	✓	✓	✓
	-40 ~ +85	X	X	X	ASK	ASK	✓

✓ = available, x = not available, ASK = call Technical Sales

EMV42GT - OUTLINES AND DIMENSIONS



VEMV42GT VOLTAGE CONTROL SPECIFICATION

Control Voltage:	Standard = $+1.5 \pm 1.0$ Volts for all input voltages. (Contact technical sales if $+2.5 \pm 2.0$ Volts is required.)
Frequency Deviation:	± 6.0 ppm min. ($V_{con} = +4.5V \pm 1.0V$)
Slope Polarity:	Positive (increase of control voltage increases output frequency.)
Input Impedance:	2M Ω minimum
Modulation Bandwidth:	25kHz minimum
Linearity:	$\pm 10\%$ maximum

SSB PHASE NOISE at 25 $^\circ\text{C}$

Offset		10Hz	100Hz	1kHz	10kHz	100kHz
Part = EMV42GT33	at 77.760MHz (dBc/Hz)	-80	-110	-135	-130	-132
	at 155.520MHz (dBc/Hz)	-80	-110	-125	-120	-125

PART NUMBERING SCHEDULE

Example: **EMV42GT33-200.00-2.5/-30+75**

Series Description
 TCXO = EMV42GT*
 VCTCXO = VEMV42GT

Supply Voltage
 33 = 3.3 VDC

Frequency (MHz)
 200.00

Stability over OTR (\pm ppm)
 2.5

Operating Temperature Range (OTR) ($^\circ\text{C}$)
 -30 +75

Lower and upper limits

* Note, 'G' indicates RoHS Compliant part