







UNCONTROLLED DOCUMENT

PART NUMBER
OED-CL-23F-TR

REV.
B



CATHODE \ominus ANODE \oplus



REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #10510.	4.29.99
B	E.C.N. #10BRDR. & REDRAWN IN 3D.	12.19.02

ELECTRO-OPTICAL CHARACTERISTICS $T_A=25^\circ\text{C}$ $I_f=20\text{mA}$

PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		880		nm	
SPECTRAL BANDWIDTH		70		nm	
FORWARD VOLTAGE		1.3	1.5	V _f	
REVERSE VOLTAGE	5.0			V _r	I _r =10µA
RADIANT INTENSITY		1.9		mW/SR	I _f =50mA
HALF ANGLE		±50		degrees	
EPOXY LENS FINISH: WATER CLEAR					

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	1	A
STEADY CURRENT	50	mA
POWER DISSIPATION	80	mW
DERATE FROM 25°C	-1.2	mW/°C
OPERATING TEMP.	-20 TO +70	°C
STORAGE TEMP.	-30 TO +80	°C

* $t_p < 100\mu\text{s}$, $t_p/T = 0.01$

NOTES:

- 3,000 PARTS PER REEL.
- THE POLARITY MARK IS ORIENTED AWAY FROM THE TAPE SPROCKET HOLE.

UNCONTROLLED DOCUMENT

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.038), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION -0.00 MAX= +0.00 -DECIMAL PRECISION

REV. B	PART NUMBER OED-CL-23F-TR
-----------	------------------------------

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

880nm CERAMIC SURFACE MOUNT INFRARED LED,
WATER CLEAR LENS, TAPE AND REEL.

DRAWN BY: BC	CHECKED BY:	APPROVED BY:	DATE: 12.23.97 PAGE: 1 OF 1 SCALE: N/A
-----------------	-------------	--------------	--