

P-tec Corp. Tel:(800)688-0613  
 2405 Commerce Circle Tel:(719) 589 3122  
 Alamosa Co. 81101 Fax:(719) 589 3592  
 www.p-tec.net sales@p-tec.net



## PL523 Series 5mm LED Panel Mount Metal Holder

### Features

- \*Panel Mount Indicator with Inner Reflector
- \*Chrome or Black Finish
- \*Mounting Hole 8 mm (0.315")
- \*Mounting Hardware Included
- \*1 Green LED with Color Diffused Lens used
- \*26AWG Red (+) and Black (-) 6" Wire Leads
- \*RoHS Compliant

### Absolute Maximum Ratings at T<sub>A</sub> = 25°C

Power Dissipation.....	78mW
Reverse Voltage (<100µA).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25°C to +85°C
Storage Temperature Range.....	-40°C to +100°C
Soldering Temperature (1.6 mm below body).....	260°C for 5 seconds

### Electrical & Optical Characteristics at T<sub>A</sub> = 25°C

Part Number Add <b>S</b> for Chrome Finish Add <b>B</b> for Black Finish	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2θ ½	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
6" Wire Leads			nm	nm	Deg				
PL523-1G13-2	Green	GaP	567	572	35°	2.1	2.6	17.0	30.0

All dimensions are in Millimeters. Tolerance is ± 0.25mm unless otherwise specified.

