



Power Divider



H3



H4

Flatpack

3-way 0° 1 to 1000MHz

P/N	Freq. Range (MHz) f _L -f _U	Insertion Loss (dB)			Isolation (dB)			VSWR		Unbalance		Case	
		L	M	U	L	M	U	Max		Phase (°)	Amp. (dB)		
		Typ/Max	Typ/Max	Typ/Max	Typ/Min	Typ/Min	Typ/Min	In	Out	Max	Max		
JXWBGF-H-3-1-300	1-300	0.3/0.6	0.3/0.6	0.6/1.2	35/30	30/20	25/20					0.4	H4
JXWBGF-H-3-25-1000	25-1000	0.3/0.8	0.3/0.8	0.8/1.2	25/15	30/20	35/14			4		0.5	H4

Notes:

1. Operating Temperature : -40 °C to +80 °C. Storage Temperature : -55 °C to +85 °C.
2. L=low range [f_L to 10 f_L] M=mid range [10 f_L to f_U/2] U=upper range[f_U/2 to f_U]

4-way 0° 1 to 200MHz

P/N	Freq. Range (MHz) f _L -f _U	Insertion Loss (dB)			Isolation (dB)			VSWR		Unbalance		Case	
		L	M	U	L	M	U	Max		Phase (°)	Amp. (dB)		
		Typ/Max	Typ/Max	Typ/Max	Typ/Min	Typ/Min	Typ/Mi	In	Out	Max	Max		
JXWBGF-H-4-1-200	1-200	0.8/1.0	0.8/1.0	0.8/1.2	25/20	25/20	25/20			4		0.4	H3

Notes:

1. Operating Temperature : -40 °C to +80 °C. Storage Temperature : -55 °C to +85 °C.
2. L=low range [f_L to 10 f_L] M=mid range [10 f_L to f_U/2] U=upper range[f_U/2 to f_U]
3. Custom Designs Available