

MULTI-MODE ULTRA-MINI 1x1, 1x2, 2x2 (ADD/DROP) FIBER-OPTIC SWITCH

OFMSMM Series

Product Description

Oplink OFMS ultra-mini fiber-optic switches are ideal for module and system integration where the unique unilateral input and output fiber configuration is preferred. These switches are designed for use in re-configurable optical add/drop multiplexers, optical cross-connect systems, and network switching for fault protection applications.

The opto-mechanical ultra-mini switch can be directly mounted on printed circuit board (PCB) and offer the same excellent performance characteristics of Oplink's standard OFMS series switch products. The OFMS miniature switches are designed to exceed Telcordia standards GR-1221 and GR-1073.

Oplink provides customized design to meet special control and applications. Also, Oplink offers modular assemblies that integrate other components to form a full function module or subsystem.

Performance Specification

Parameters		Min	Typ.	Max	Unit
Wavelength Range (λ_{op})		770 ~ 860 and/or 1260 or 1360			nm
Insertion Loss ¹	1x1, 1x2	< 0.5			dB
	2x2AD	< 0.6			
Return Loss		> 30			dB
Channel Cross-talk		> 35			dB
Repeatability		±0.05			dB
Switching Speed ²		< 4			ms
Operating Voltage		5 ± 10%			VDC
Driving Current ³	Latching	22	32		mA
	Non-latching	31	46		
Coil Resistance	Latching	205.5 ± 10%			Ω
	Non-latching	145 ± 10%			
Cycle Rate		≤10			Hz
Durability		10 ⁷			cycle
Operating Power Handling		500			mW
Operating Temperature (T_{op})		0	70		°C
Storage Temperature		-40	80		°C
Humidity ⁴		<85% RH, or <90%RH for short term			
Switch Relay Type		latching or non-latching, single coil			
Fiber Type		50μm or 62.5μm core multi-mode fiber			
Nominal Package Size	Bare Fiber Pigtail	29 (L) x 10.5 (W) x 8.0 (H)			mm
	900μm Loose Tube Pigtail	38.5 (L) x 10.5 (W) x 8.0 (H)			mm

Notes:

1) Excluding connectors; add 0.3 dB within λ_{op} and T_{op} . Based on FOTP-34 method A, steady state equilibrium launch conditions. Measured using 850nm and 1310nm multi-mode light source.

2) Switching time is defined as the time interval between electrical trigger and 90% of stable optical output.

3) A >20ms DC pulse is recommended for latching type of switch.

4) Short term is defined as less than 96 consecutive hours and less than a total of 15 days over a one year period.




Features

- ◆ Miniature Size
- ◆ Unilateral Input/output Fiber Configuration
- ◆ Bi-directional Operation
- ◆ 1x1, 1x2 latching or non-latching configurations
- ◆ Wide Operating Wavelength Range
- ◆ Seam-seal Package
- ◆ Highly Stable & Reliable


Applications

- ◆ Network Switching
- ◆ Network Protection and Restoration
- ◆ Instrumentation, Testing and Measurement


Function Diagram



1x1 On/Off Switch



1x2 Switch



2x2 Add/Drop Switch

Ordering Information

Oplink can provide a remarkable range of customized optical solutions. For detail, please contact Oplink's OEM design team or account manager for your requirements and ordering information (510) 933-7200.

