



Features

- Frequency Range: 100~3000MHz
- Standard Hermetic Package TO-8C
- Operating Temperature Range: -55°C ~ +85°C


Specifications (50 Ω, V_{CC} = +12V, T_A = -55°C ~ +85°C)

Parameter	Symbol	Unit	Guaranteed	Typical
Frequency Range	f _L ~f _H	MHz	100~3000	100~3000
Gain	G _p	dB	11.0	12.5
Gain Flatness	ΔG _p	dB	1.5	1.0
Noise Figure	F _n	dB	3.5Δ #	2.7
Input VSWR	VSWR _i	---	2.0:1Δ	1.6:1
Output VSWR	VSWR _o	---	2.0:1Δ	1.4:1
Output Power @ 1dB Compression	P ₋₁	dBm	24.0Δ	25.0
DC Current	I _{cc}	mA	---	150

“Δ” T_A = 24 ± 1°C;


Maximum Rating

DC Voltage : +13.5V_{DC}
 RF Input: +15dBm
 Storage Temp: +125°C



Application Notes

1. Typical application shown as right, C₁ = 10~33 μF ; C₂ = 3300~6800pF;
2. See assembly section for mounting information
3. Connectorized package(SMA-1) available
4. ESD observe handling precautions



Typical Curves

