



features


- Excellent anti-sulfuration characteristic due to using high sulfuration-proof inner top electrode material
- Superior to RK73 series chip resistors in pulse withstanding voltage
- Suitable for both flow and reflow soldering
- Marking: White three-digit on wine red protective coat
- Products with lead-free terminations meet EU RoHS requirements. Pb located in glass material, electrode and resistor element is exempt per Annex 1, exemption 5 of EU directive 2005/95/EC



dimensions and construction



Derating Curve



Type (Inch Size Code)	Dimensions inches (mm)				
	L	W	c	d	t
1J (0603)	.063±.008 (1.6±0.2)	.031±.004 (0.8±0.1)	.012±.004 (0.3±0.1)	.012±.004 (0.3±0.1)	.018±.004 (0.45±0.1)
2A (0805)	.079±.008 (2.0±0.2)	.049±.004 (1.25±0.1)	.016±.008 (0.4±0.2)	.012 ^{+0.008} _{-.004} (0.3 ^{+0.2} _{-.1})	.02±.004 (0.5±0.1)
2B (1206)	.126±.008 (3.2±0.2)	.063±.008 (1.6±0.2)	.02±.012 (0.5±0.3)	.016 ^{+0.008} _{-.004} (0.4 ^{+0.2} _{-.1})	.024±.004 (0.6±0.1)
2E (1210)	.102±.008 (2.6±0.2)				
W2H (2010)	.197±.008 (5.0±0.2)	.098±.008 (2.5±0.2)			
W3A (2512)	.248±.008 (6.3±0.2)	.122±.008 (3.1±0.2)		.026±.006 (0.65±0.15)	

ordering information

New Part #	SG73	2A	RT	TD	103	K
Type	SG73					
Power Rating		1J 2A 2B 2E W2H W3A				
Termination Material			RT: Sn Anti-Sulfur			
Packaging				TP: 0603, 0805: 7" 2mm pitch punch paper TD: 0603, 0805, 1206, 1210: 7" 2mm pitch punched paper TDD: 0603, 0805, 1206, 1210: 10" paper tape TE: 0805, 1206, 1210, 2010 & 2512: 7" punched plastic TED: 0805, 1206, 1210, 2010 & 2512: 10" punched plastic For further information on packaging, please refer to Appendix A		
Nominal Resistance					±10%, ±20%: 2 significant figures + 1 multiplier "R" indicates decimal on value <10Ω	
Resistance Tolerance						K: ±10% M: ±20%

Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.

11/07/08

applications and ratings

Part Designation	Power Rating	T.C.R. (ppm/°C) Max.	Resistance Range		Maximum Working Voltage	Maximum Overload Voltage	Rated Ambient Temperature	Operating Temperature Range
			(E-12) (K±10%)	(E-12) (M±20%)				
1J (0603)	0.1W	±400	1Ω - 8.2Ω		50V	100V	+70°C	-55°C to +155°C
		±200	10Ω - 1MΩ					
2A (0805)	0.125W	±400	1Ω - 8.2Ω		150V	200V	+70°C	-55°C to +155°C
		±200	10Ω - 1MΩ					
2B (1206)	0.25W	±400	1Ω - 8.2Ω		200V	400V	+70°C	-55°C to +155°C
		±200	10Ω - 1MΩ					
2E (1210)	0.33W	±400	1Ω - 8.2Ω		200V	400V	+70°C	-55°C to +155°C
		±200	10Ω - 1MΩ					
W2H (2010)	0.75W	±400	1Ω - 8.2Ω		200V	400V	+70°C	-55°C to +155°C
		±200	10Ω - 1MΩ					
W3A (2512)	1W	±400	1Ω - 8.2Ω		200V	400V	+70°C	-55°C to +155°C
		±200	10Ω - 1MΩ					

environmental applications

Performance Characteristics

Parameter	Requirement Δ R		Test Method
	Limit	Typical	
Resistance	Within specified tolerance	—	25°C
T.C.R.	Within specified T.C.R.	—	+25°C/-55°C and +25°C/+125°C
Overload (Short time)	±2%	±0.5%	Rated Voltage x 2.5 for 5 seconds
Resistance to Solder Heat	±1%	±0.75%	260°C ± 5°C, 10 seconds ± 1 second
Rapid Change of Temperature	±0.5%	±0.3%	-55°C (30 minutes), +125°C (30 minutes), 100 cycles
Moisture Resistance	±3%	±0.75%	40°C ± 2°C, 90%~95%RH, 1000 hours; 1.5 hr ON, 0.5 hr OFF cycle
Endurance at 70°C	±3%	±0.75%	70°C ± 2°C, 1000 hours, 1.5 hr ON, 0.5 hr OFF cycle
High Temperature Exposure	±1%	±0.5%	+155°C, 1000 hours
Sulfuration Test	—	±0.5%	H ₂ S 1000ppm, +25°C, 90%Rh, 720 hours

Additional environmental applications can also be found at www.koaspeer.com

Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.

11/07/08