



5	EUPV15B015006K	TUBE $\varnothing$ 1.5MM*6MM	2PCS
4	8002A-04G2	MINI USB 4P.CONN SUYIN P/N:8002-G2-02 8002-G2-01 8002-04-K 8002-NI-13	1PCS
3	EZPVC50PR9011ZH	PVC MOLDING 50P COLOR:BLACK RAL9011,LSZH	10GR
2	ECUSB04M0017	USB A PLUG GOLD FLASH LENGTHEN MODEL PSATERN CORE:WHITE	1PCS
1	EK2804BK350024	CABLE UL2835 28AWG*1P+28AWG*2C+AEB OD=3.5mm COLOR:BLACK BRAID ON TOP OF 65 % 2.0REV TKS OR LOCAT EQUALITY	1230MM
NO	PART P/N.	SPECIFICATION	Q'TY
MATERIAL SPECIFICATION			

NOTES:  
 ELECTRIC TEST  
 1.TEST OPEN,SHORT,MISWIRE.  
 2.CONTACT RESISTANCE:2 OHM MAX.  
 3.INSULATION RESISTANCE:10M OHM MIN.  
 4.HI-POT TEST:DC 300V 0.1A 3SEC.  
 5.CPK Measure point Y1-Y3.

2				
1				
NO.	DESCRIPTION	MATERIAL	COLOR	REMARK

**SUYIN**  
CONNECTOR

CUSTOMER COPY TITLE: USB+MINI 4P+CBL1.2M

PART NO. CBL30071-1200

PART NO. (OLD) \_\_\_\_\_

DRAWING NO.  $\frac{D}{ING}$  CBL30071-1200

SCALE FREE UNIT mm A4

						Angle	$\pm 2^\circ$	DRAW		
						30 ~	$\pm 0.50$	DESIGN		
						10 ~ 30	$\pm 0.30$	CHECK		
						~ 10	$\pm 0.15$	APPRO.		
ECN (DCN) NO.	REV	DATE	DESCRIPTION	CHANGE	APPRO.	GENERAL TOLERANCE UNLESS OTHERWISE NOTED		APPRO.		