

P-tec Corp. Tel:(800)688-0613
 2405 Commerce Circle Tel:(719) 589 3122
 Alamosa Co. 81101 Fax:(719) 589 3592
 www.p-tec.net sales@p-tec.net



PL16 Series 5mm (T1¾) Ultra Bright White LED

Features

- *Popular T1 3/4 style Lens
- *High intensity
- *Narrow Viewing Angle
- *Integrated Zener Diode for ESD protection
- *RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

| | |
|--|---------------------|
| Power Dissipation | 120mW |
| Reverse Voltage (<100µA)..... | 5.0V |
| Max Forward Current..... | 30mA |
| Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)..... | 100mA |
| Operating Temperature Range | -25°C to +85°C |
| Storage Temperature Range..... | -40°C to +100°C |
| Soldering Temperature (1.6mm below body)..... | 260°C for 5 seconds |
| Electrostatic Discharge (ESD)..... | 2000V |

Electrical & Optical Characteristics at T_A = 25°C

| Part Number | Emitting Color | Chip Material | Chromaticity Coordinates | | View Angle 2θ ½ | Forward Voltage @20mA (V) | | Luminous Intensity @20mA (mcd) | |
|------------------|----------------|---------------|--------------------------|------|--------------------|------------------------------|-----|-----------------------------------|------|
| | | | X | Y | | Typ | Max | Min | Typ |
| Water Clear Lens | | | X | Y | Deg | Typ | Max | Min | Typ |
| PL16C-WCW09Z | White | InGaN | 0.31 | 0.30 | 15° | 3.2 | 4.0 | 4800 | 9000 |

All dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified. An epoxy meniscus may extend about 1mm down the leads.

