



DESCRIPTION

The SG1536 series of monolithic amplifiers is designed specifically for use in high voltage applications up to $\pm 40V$ and where high common-mode input ranges, high output voltage swings, and low input

currents are required. These devices are internally compensated and are pin compatible with industry standard operational amplifiers.

KEY FEATURES


- High Supply Voltage Capability
- High Output Voltage Swing
- High Common-Mode Voltage Range
- Internal Frequency Compensation
- Input Current 35nA Maximum Over Temperature

HIGH RELIABILITY FEATURES


- Available to MIL-STD-883D and DESC SMD
- Microsemi LEVEL "S" Processing Available

IMPORTANT: For the most current data, consult MICROSEMI's website: <http://www.microsemi.com>

PRODUCT HIGHLIGHT



M Package: RoHS / Pb-free 100% Matte Tin Lead Finish†



PACKAGE ORDER INFO

T_A (°C)	M Plastic DIP 8-Pin	Y Plastic DIP 8-Pin	T TO-99 Metal Can 8-Pin
	RoHS Compliant / Pb-free Transition DC: 0503*		
0 to 70	SG1436M	SG1436Y	SG1436T
-55 to 125	-	SG1536Y	SG1536T
MIL-STD-883	-	SG1536Y/883B	SG1536T/883B
DESC	-	SG1536Y/DESC	SG1536T/DESC

Note: Available in Tape & Reel. Append the letters "TR" to the part number. (i.e. SG1536Y-TR)
†Peak Package Solder Reflow Temperature (40 seconds maximum exposure) 260°C (+0, -5)

HIGH-VOLTAGE OPERATIONAL AMPLIFIER

DESCRIPTION

The SG1536 series of monolithic amplifiers is designed specifically for use in high voltage applications up to $\pm 40V$ and where high common-mode input ranges, high output voltage swings, and low input currents are required. These devices are internally compensated and are pin compatible with industry standard operational amplifiers.

FEATURES


- High supply voltage capability
- High output voltage swing
- High common-mode voltage range
- Internal frequency compensation
- Input current 35nA maximum over temperature

HIGH RELIABILITY FEATURES

-SG1536

- ♦ Available to MIL-STD-883 and DESC SMD
- ♦ SG level "S" processing available

CIRCUIT SCHEMATIC



ABSOLUTE MAXIMUM RATINGS (Note 1)

Supply Voltage

SG1536 ±40V

SG1436 ±34V

Differential Input Signal

±(V⁺ + |V⁻| - 3) V

Common-Mode Input Swing

±V⁺, -(|V⁻| - 3) V

Output Short Circuit Duration

(V⁺ = |V⁻| = 28V, V_O = 0V) 5.0sec



Operating Junction Temperature

Hermetic (T, Y-Package) 150°C

Storage Temperature Range -65°C to 150°C

Lead Temperature (Soldering, 10 Seconds) 300°C

Note 1. Exceeding these ratings could cause damage to the device.

THERMAL DERATING CURVES**RECOMMENDED OPERATING CONDITIONS** (Note 2)

Supply Voltage

SG1536 ±28V

SG1436 ±15V

Operating Ambient Temperature Range (T_A)

SG1536 -55°C to 125°C

SG1436 0°C to 70°C

Note 2. Range over which the device is functional.






ELECTRICAL SPECIFICATIONS(Unless otherwise specified, these specifications apply for the operating ambient temperature of T_A = 25°C, and V_S = ±28V. Low duty cycle pulse testing techniques are used which maintains junction and case temperatures equal to the ambient temperature.)

Parameter	Test Conditions	SG1536			SG1436			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
Input Offset Voltage	T _A = T _{MIN} to T _{MAX}	2.0	5.0	10	5.0	10	10	mV
Input Offset Current	T _A = T _{MIN}	1.0	3.0	5.0	5.0	10	10	nA
	T _A = T _{MAX}	7.0	14	14	7.0	14	14	nA
Input Bias Current	T _A = T _{MIN} to T _{MAX}	4.5	8.0	20	15	40	55	nA
Differential Input Impedance	Open loop, ≤ 5.0Hz	10	10	10	250	250	250	MΩ
Common-Mode Input Impedance	f ≤ 5.0Hz	250						MΩ
Common-Mode Input Voltage Range (Peak)		±24	±25	±25	±22	±25	±25	V
Common-Mode Rejection Ratio	R _L = 10KΩ, V _O = ±10V	80	110	70	100	100	100	dB
Large Signal Voltage Gain	R _L = 100KΩ, V _O = ±10V	100K	200K	70K	200K	200K	200K	V/V
	T _A = T _{MIN} to T _{MAX}	500K	500K	500K	500K	500K	500K	V/V
Power Supply Rejection Ratio	V ⁺ constant, R _S ≤ 10KΩ	15	100	15	35	200	200	μV/V
	V ⁻ constant, R _S ≤ 10KΩ	15	100	35	35	200	200	μV/V
Output Impedance	f ≤ 5.0Hz	1.0	1.0	1.0	1.0	1.0	1.0	KΩ
Short Circuit Output Current	R _L = 5.0 KΩ, V _S = ±28V	±17	±17	±17	±17	±17	±17	mA
Output Voltage Swing (Peak)	R _L = 5.0 KΩ, V _S = ±36V	±30	±30	±30	±30	±30	±30	V
		±30	±30	±30	±30	±30	±30	V

ELECTRICAL SPECIFICATIONS (continued)

Parameter	Test Conditions	SG1536			SG1436			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
Power Bandwidth	$A_v = +1, R_s = 5.0\text{K}\Omega, \text{THD} \leq 5\%$, $V_o = 40\text{V p-p}$		23			23		KHz
Unity Gain Crossover Frequency	Open loop		1.0			1.0		MHz
Slew Rate	Unity gain		2.0			2.0		V/ μ s
Phase Margin	Open loop, unity gain		50			50		deg
Gain Margin			18			18		dB
Equivalent Input Noise	$A_v = 100, R_s = 10\text{K}\Omega, f = 1.0\text{KHz},$ BW = 1.0 Hz		50			50		nV/ $\sqrt{\text{Hz}}$
Power Supply Current			2.2	4.0		2.6	5.0	mA
Power Consumption	$V_o = 0$	124	224		146	280		mW

CHARACTERISTIC CURVES

FIGURE 1.
POWER BANDWIDTHFIGURE 2.
PEAK OUTPUT VOLTAGE SWING VS.
POWER SUPPLY VOLTAGEFIGURE 3.
OPEN-LOOP FREQUENCY RESPONSEFIGURE 4.
OUTPUT SHORT-CIRCUIT CURRENT VS.
TEMPERATUREFIGURE 5.
INPUT BIAS CURRENT VS.
TEMPERATURE

TYPICAL APPLICATIONS




FIGURE 6 - VOLTAGE OFFSET NULL CIRCUIT




FIGURE 7 - DIFFERENTIAL AMPLIFIER WITH ±20V COMMON-MODE INPUT VOLTAGE RANGE




FIGURE 8 - LOW-DRIFT SAMPLE AND HOLD




FIGURE 9 - TYPICAL NON-INVERTING X10 VOLTAGE AMPLIFIER




FIGURE 10 - VOLTAGE CONTROLLED CURRENT SOURCE OR TRANSCONDUCTANCE AMPLIFIER WITH 0 TO 40V COMPLIANCE

CONNECTION DIAGRAMS & ORDERING INFORMATION (See Notes Below)

Package	Part No.	Ambient Temperature Range	Connection Diagram
8-PIN METAL CAN T - PACKAGE	SG1536T/883B SG1536T SG1436T	-55°C to 125°C -55°C to 125°C 0°C to 70°C	
8-PIN CERAMIC DIP Y- PACKAGE	SG1536Y/883B SG1536Y SG1436Y	-55°C to 125°C -55°C to 125°C 0°C to 70°C	

Note 1. Contact factory for JAN and DESC product availability.
 2. All packages are viewed from the top.