

## Features

- Frequency Range: 0.8~3.5GHz
- Standard Hermetic Package
- Operating Temperature Range: -55°C ~ +85°C

## Specifications (50 Ω, V<sub>CC</sub> = +12V, T<sub>A</sub> = -55°C ~ +85°C)

Parameter	Symbol	Unit	Guaranteed	Typical
Frequency Range	f <sub>L</sub> ~f <sub>H</sub>	GHz	0.8~3.5	0.8~3.5
Gain	G <sub>p</sub>	dB	≥12.0	13.0
Gain Flatness	ΔG <sub>p</sub>	dB	≤±0.75 Δ	±0.5
Noise Figure	F <sub>n</sub>	dB	≤4.0 Δ	2.3
Input VSWR	VSWR <sub>i</sub>	--	≤2.0:1 Δ	1.7:1
Output VSWR	VSWR <sub>o</sub>	--	≤2.0:1 Δ	1.8:1
Output Power @ 1dB Compression	P <sub>-1</sub>	dBm	≥13.0 Δ	15.5
DC Current	I <sub>CC</sub>	mA	--	35


“Δ” T<sub>A</sub> = 24 ± 1°C;

## Maximum Rating


DC Voltage : +13.5VDC

RF Input: +13dBm

Storage Temp: +125°C




TO-8C



SMO-8C

## Application Notes

1. Typical application shown as right, C<sub>1</sub> = 10~33 μF ; C<sub>2</sub> = 3300~6800pF;
3. See assembly section for mounting information
4. Connectorized package(SMA-1) available
5. ESD observe handling precautions



## Typical Curves

