


- 1 Substrate: 1.59mm \pm 0.18mm [0.0625" \pm 0.007"] FR4/G10 or equivalent high temp material. 17 μ m [1/2 oz.] Cu clad. SnPb plating.
- 2 Substrate: 3.18mm \pm 0.18mm [0.125" \pm 0.007"] FR4/G10 or equivalent high temp material. Non-clad.
- 3 Pins: material- Brass Alloy 360 1/2 hard; finish- 0.25 μ m [10 μ "] Au over 1.27 μ m [50 μ "] Ni (min.).
- 4 Pins: shell material- Brass Alloy 360 1/2 hard; finish- 0.25 μ m [10 μ "] Au over 1.27 μ m [50 μ "] Ni (min.). Contact material- BeCu; finish 0.25 μ m [10 μ "] Au over 2.54 μ m [100 μ "] Ni (min.).
- 5 Leads: material- BeCu Alloy 194; plating- 60/40 SnPb 3.80-10.16 μ m [150-400 μ "].
- 6 Test points: material- Phosphor Bronze; plating- Sn over 1.27 μ m [50 μ "] Ni. Gold flash on contact end.

Description: CARRIER ADAPTOR
 84 position PLCC ZIF socket with test points to 84 position PLCC plug.

Tolerances: diameters \pm 0.03mm [\pm 0.001"], PCB perimeters \pm 0.13mm [\pm 0.005"], PCB thicknesses \pm 0.18mm [\pm 0.007"], pitches (from true position) \pm 0.08mm [\pm 0.003"], all other tolerances \pm 0.13mm [\pm 0.005"] unless stated otherwise.

	CA-PLCC084-Z-P-T-01 Dwg	Status: Released	Scale: 4:3	Rev: D
	© 1993 IRONWOOD ELECTRONICS, INC. PO BOX 21151 ST. PAUL, MN 55121 Tele: (651) 452-8100 www.ironwoodelectronics.com	Drawing: 6/10/93	Date: 9/30/96	
		FileCA-PLCC084-Z-P-T-01 Dwg	Modified:3/31/00	