


CRYSTAL CONTROLLED OSCILLATORS

3.3V 14 PIN DIP FIXED FREQUENCY LVCMOS TCXO



HTFL546G

ABSOLUTE MAXIMUM RATINGS

TABLE 1.0

PARAMETER	UNITS	MINIMUM	NOMINAL	MAXIMUM	UNITS	NOTE
Storage Temperature		-40	-	85	°C	
Supply Voltage	(Vcc)	-0.5	-	7	Vdc	

OPERATING SPECIFICATIONS

TABLE 2.0

PARAMETER		MINIMUM	NOMINAL	MAXIMUM	UNITS	NOTE
Frequency Range	(Fo)	1.544	-	77.76	MHz	
Frequency Tolerance		-4.6	-	4.6	ppm	1
Operating Temperature Range		0	-	70	°C	
Supply Voltage	(Vcc)	3.135	3.3	3.465	Vdc	
Supply Current	(Icc)	-	9	25	mA	
Jitter (BW=10Hz to 20MHz)		-	-	5	ps rms	
Jitter (BW=12kHz to 20MHz)		-	-	1	ps rms	
SSB Phase Noise at 10Hz offset		-	-80	-		
SSB Phase Noise at 100Hz offset		-	-100	-	dBc/Hz	
SSB Phase Noise at 1KHz offset		-	-125	-	dBc/Hz	
SSB Phase Noise at 10KHz offset		-	-135	-	dBc/Hz	
SSB Phase Noise at 100KHz offset		-	-145	-	dBc/Hz	

LVCMOS OUTPUT CHARACTERISTICS

TABLE 3.0

PARAMETER		MINIMUM	NOMINAL	MAXIMUM	UNITS	NOTE
LOAD		-	-	15	pF	
Voltage (High)	(Voh)	2.2	2.4	-	Vdc	
(Low)	(Vol)	-	0.3	0.4	Vdc	
Current (High)	(Ioh)	-4	-	-	mA	
(Low)	(Iol)	-	-	4	mA	
Duty Cycle at 50% of Vcc		45	50	55	%	
Rise / Fall Time 10% to 90%			3	5	nS	

PACKAGE CHARACTERISTICS

TABLE 4.0

Package	Hermetically sealed, metal package.
---------	-------------------------------------

Note:

- Inclusive of calibration, frequency vs. temperature stability, supply voltage change, load change, shock and vibration, 20 years aging.

DESCRIPTION

The Connor Winfield HTFL546G is a 3.3V LVCMOS, hermetically sealed, fixed frequency, Temperature Compensated Crystal Oscillator (TCXO). The HTFL546G is designed for use as a SONET/SDH Network Timing Source.

FEATURES

3.3V OPERATION

LVCMOS OUTPUT

LOW JITTER <1ps RMS

OVERALL FREQUENCY TOLERANCE:
±04.6ppm

TEMPERATURE RANGE: 0 to 70°C

HERMETICALLY SEALED PACKAGE

RoHS COMPLIANT / LEAD FREE

ORDERING INFORMATION

HTFL546G - 1.544 MHz

TCXO
SERIES

CENTER
FREQUENCY

Specifications subject to change without notice.

