

# RL201 THRU RL207

## GENERAL PURPOSE PLASTIC RECTIFIERS


Reverse Voltage – 50 to 1000 Volts

Forward Current – 2.0 Amperes

DO-15

### Features

- High surge current capability
- 2.0 ampere operation at  $T_A = 75^\circ\text{C}$  with no thermal runaway
- Low reverse leakage
- Construction utilizes void-free molded plastic technique.
- High temperature soldering guaranteed:  
250°C/10 seconds, 0.375" (9.5mm) lead length,  
5 lbs (2.3kg) tension



Dimensions in mm

### Mechanical Data


- **Case:** Molded plastic, DO-15.
- **Terminals:** Plated axial leads, solderable per MIL-STD-750, method 2026
- **Polarity:** Color band denotes cathode end.
- **Mounting Position:** Any.

### Absolute Maximum Ratings and Characteristics @ 25 °C unless otherwise specified.

	Symbols	RL201	RL202	RL203	RL204	RL205	RL206	RL207	Units
Maximum repetitive peak reverse voltage	$V_{RRM}$	50	100	200	400	600	800	1000	Volts
Maximum RMS voltage	$V_{RMS}$	35	70	140	280	420	560	700	Volts
Maximum DC blocking voltage	$V_{DC}$	50	100	200	400	600	800	1000	Volts
Maximum average forward current at $T_A = 75^\circ\text{C}$	$I_{(AV)}$	2							Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (MIL-STD-750D 4066 method)	$I_{FSM}$	70							Amps
Maximum instantaneous forward voltage at $I_{FM} = 2.0A$ , $T_A = 25^\circ\text{C}$ (Note 2)	$V_F$	1							Volts
Maximum DC reverse current at rated DC blocking voltage	$I_R$	5							$\mu\text{A}$
Typical thermal resistance	$R_{\theta JA}$	40							$^\circ\text{C}/\text{W}$
Typical junction capacitance (Note 1)	$C_J$	20							pF
Operating and storage temperature range	$T_J, T_S$	-65 to +175							$^\circ\text{C}$

### Notes:

- (1) Measured at 1MHz and applied reverse voltage of 4volts
- (2) Pulse test: pulse width 300 uSec, Duty cycle 1%.



**SEMTECH ELECTRONICS LTD.**

(Subsidiary of Semtech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002  
Certificate No. 05103



ISO 14001  
Certificate No. 7116



ISO 9001 : 2000  
Certificate No. 550-159-04-002-04

Dated : 27/02/2003