

Product SKU: C1320.21.01
Product Description: Hook-Up Wire, PVC Test Lead, No. of Conductors: 1, Gauge Size (AWG): 18, Conductor/Strands: 65/36, Temperature Range: -25Â°C to +60Â°C - Black - 1000 Ft. Spool
Product Category: Electronics - Hook-Up Wire - Rubber/PVC Test Lead - PVC Test Lead - Black

**Product Construction:**

- Conductor:
- Fully-annealed, stranded tinned copper per ASTM B-33
- Insulation:
- Temperature range: -25Â°C to +60Â°C PVC
 - Premium grade color coded Polyvinylchloride (PVC)

Product Specification:

- No. of Conductors:
- 1
- Conductor Size (AWG):
- 18
- Conductor/Strands:
- 65/36
- Jacket Color:
- Black
- Nominal Insulation Thickness (in):
- 0.045
- Nominal Insulation Thickness (mm):
- 1.14
- Breakdown Voltage (AC,ms):
- 20,000V
- Working Voltage:
- 5,000V
- Nominal Outside Diameter (in):
- 0.140
- Nominal Outside Diameter (mm):
- 3.56
- Standard Packaging:
- 1000' Spool

- Standard Package Quantity: • 1
- UPC #: • 079407815128
- Footnote: • For intermittent duty only.
- Put-up: • 1000
- SCC-14: • 50079407815122
- Cube: • 533.12
- Weight Per Unit of Measure: • .01
- ColorOption: • Black

Product Information:

- Applications: • Oscillators
- Test equipment
- Packaging: • 1000' (305 m) Spools
- 500' (152m) Reels
- 5000' (1524m) Reels
- Other put-ups available- consult Customer Service

Reference Charts

[Color Code Chart](#)

Technical Specifications

[Unit Conversion Factors](#)

[Cable Design Equations - Balanced Pair](#)

[Insulation and Jacket Properties](#)

[Temperature Conversion Chart](#)

[Decimal and Unit Conversion Factors](#)

[Cable Design Equations - Braid Shield](#)

[AWG Conductor Chart](#)

[Conduit Capacity Chart](#)

[Cable Design Equations - Coaxial Cable](#)

[Engineering Prefixes](#)

[Coax Connector Cross Reference](#)

[Glossary](#)

**CAROL
BRAND**