


2A-N

1.0 TO 1.5 WATT DC-DC CONVERTERS



Feature

- 24-Pin DIP Package
- Pi Input Filter
- Unregulated Outputs
- Low Ripple and Noise
- 70% Efficiency

MODEL NUMBER	INPUT VOLTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT	INPUT CURRENT		CASE
				NO LOAD	FULL LOAD	
2A-01N	5 VDC	5 VDC	220mA	115 mA	330 mA	A
2A-02N	5 VDC	12 VDC	125 mA	115 mA	420 mA	A
2A-03N	5 VDC	15 VDC	100 mA	115 mA	420 mA	A
2A-04N	5 VDC	±12 VDC	±62 mA	115 mA	420 mA	A
2A-05N	5 VDC	±15 VDC	±50 mA	115 mA	420 mA	A
2A-11N	12 VDC	5 VDC	220 mA	45 mA	120 mA	A
2A-12N	12 VDC	12 VDC	125 mA	45 mA	165 mA	A
2A-13N	12 VDC	15 VDC	100 mA	45 mA	165 mA	A
2A-14N	12 VDC	±12 VDC	±62 mA	45 mA	165 mA	A
2A-15N	12 VDC	±15 VDC	±50 mA	45 mA	165 mA	A

Specifications

INPUT SPECIFICATIONS:

Input Voltage Range.....±10%
 Input Filter.....PI Type

OUTPUT SPECIFICATIONS:

Voltage Accuracy.....±3.0% max.
 Ripple and Noise, 20MHz BW¹.....100mV p-p max.
 Short Circuit Protection.....Momentary
 Line Regulation².....±1.2%
 Load Regulation³, EC2A01N.....±8.0%
 All Other Models.....±6.0%

GENERAL SPECIFICATIONS:

Efficiency.....60%-80%
 Isolation Capacitance.....30pF
 Isolation Resistance.....10⁹ohms
 Switching Frequency.....20KHz, min
 Operating Temperature Range.....-25°C to + 71°C
 Case Temperature (Plastic case).....95°C max.
 (Copper case).....100°C max.
 Cooling.....Free-Air Convection
 Storage Temperature Range.....-40°C to + 100°C
 Dimensions1.25 x 0.8 x 0.4 inches
 (31.8 x 20.3 x 10.2mm)

ISOLATION VOLTAGE:

500 VDC min.....Standard Models
 3K VDC min.....Suffix "H" Models

CASE MATERIAL:


Standard Models.....Non-Conductive Black Plastic
 Suffix "M" Models.....Black Coated Copper
 with Non-Conductive Base

NOTE:

1. 15 µF 35V, Tantalum Capacitor Across Each Output.
2. Line regulation is per 1.0% change in input voltage.
3. Load regulation is for load change from 100% to 20% See graph of load regulation.


CASE A

NOTE: Pin Size is 0.02" Inch (0.5m/m) DIA or .020 x .014 Inch
 All Dimensions In Inches(mm)



All Specifications Typical At Nominal Line,
 Full Load and 25°C Unless Otherwise Noted.

Typical Load Regulation



PIN CONNECTION

Pin	500 VDC		Pin	3K VDC	
	Single Output	Dual Output		Single Output	Dual Output
1	24	+V Input	1	2,3	+V Input
2	23	NC	2,23,24		-V Input
3	22	NC	10	11	NP
10		-V Output	12		-V Output
11		+V Output	13		+V Output
12		-V Input	14		NP
13		-V Input	15		NP
14		+V Output	16		+V Output
15		-V Output	17		+TP
					NP

*NP-NO PIN

*TP-TEST POINT

*NC-NO CONNECTION WITH PIN

*GO-GROUND