

RED LASER DIODE

DL-3147-031

SANYO

Ver.1 Apr. 2001

Features

- Short wavelength : 650 nm (Typ.)
- Low threshold current : $I_{th} = 25$ mA (Typ.)
- TE mode

Applications

Bar-code scanner

Absolute Maximum Ratings

($T_c=25^\circ\text{C}$)

Parameter		Symbol	Ratings	Unit
Light Output	CW	P_o	7	mW
Reverse Voltage	Laser	VR	2	V
	PD		30	
Operating Temperature		T_{opr}	-10 to +50	$^\circ\text{C}$
Storage Temperature		T_{stg}	-40 to +85	$^\circ\text{C}$


Electrical and Optical Characteristics⁽¹⁾⁽²⁾

($T_c=25^\circ\text{C}$)

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit
Threshold Current		I_{th}	CW	-	25	40	mA
Operating Current		I_{op}	$P_o=5\text{mW}$	-	35	50	mA
Operating Voltage		V_{op}	$P_o=5\text{mW}$	-	2.3	2.6	V
Lasing Wavelength		L_p	$P_o=5\text{mW}$	645	650	660	nm
Beam ³⁾ Divergence	Perpendicular	Q_v	$P_o=5\text{mW}$	25	30	35	$^\circ$
	Parallel	Q_h	$P_o=5\text{mW}$	7.0	8.0	10	$^\circ$
Off Axis Angle	Perpendicular	dQ_v	-	-	-	± 3	$^\circ$
	Parallel	dQ_h	-	-	-	± 2	$^\circ$
Differential Efficiency		dP_o/dI_{op}	-	0.3	0.5	0.8	mW/mA
Monitoring Output Current		I_m	$P_o=5\text{mW}$	0.1	0.2	0.4	mA
Astigmatism		A_s	$P_o=5\text{mW}$	-	8	-	μm


1) Initial values 2) All the above values are evaluated with Tottori Sanyo's measuring apparatus

3) Full angle at half maximum Note : The above product specification are subject to change without notice.




Characteristics


Output power vs. Forward current




Threshold current vs. Temperature




Monitoring current vs. Output power



Beam divergence



Lasing wavelength vs. Temperature



Lasing wavelength vs. Output power

