

POLYSTYRENE FILM CAPACITOR-PSA&PSR

Suntan®

INDUCTIVE, AXIAL AND RADIAL, WELDED LEAD STYLE


TS10

FEATURES


- Low dissipation factor and high insulation resistance.
- High stability of capacitance and DF versus temperature and frequency.
- High precision of capacitance is available

S P E C I F I C A T I O N S

OPERATING TEMPERATURE	-40°C to 70°C
RATING VOLTAGE	DC 33V, 50V, 100V, 125V, 250V, 500V, 630V
CAPACITANCE RANGE	10PF to 10000PF
CAPACITANCE TOLERANCE	±1%, ±2%, ±2.5%, ±5%, ±10%
INSULATION RESISTANCE	100000MΩ min at 25°C
DISSIPATION FACTOR	C>330PF, DF<0.1%, Q>1000 at 1KHz
TEMPERATURE COEFFICIENT	N150 ±50 ppm/°C
CAPACITORS OF OTHER SPECIFICATION ARE AVAILABLE	



TYPE:



VDC	50VDC/100VDC			160VDC			500VDC/630VDC		
	PF	D	L	Ø d	D	L	Ø d	D	L
10-56	5.5	12	0.4	5.5	12	0.4	5.5	12	0.4
68	5.5	12	0.4	5.5	12	0.4	5.5	12	0.4
82	5.5	12	0.4	5.5	12	0.4	5.5	12	0.4
100	6.0	12	0.4	5.5	12	0.4	5.5	12	0.4
120	5.5	12	0.4	5.5	12	0.4	5.5	12	0.4
150	5.5	12	0.4	5.5	12	0.4	7.5	14	0.4
180	5.5	12	0.4	5.5	12	0.4	6.0	12	0.4
220	5.5	12	0.4	5.5	12	0.4	6.0	12	0.4
270	5.5	12	0.4	5.5	12	0.4	6.0	12	0.4
330	5.5	12	0.4	5.5	12	0.4	6.5	12	0.4
390	5.5	12	0.4	5.5	12	0.4	6.5	12	0.4
470	5.5	12	0.4	5.5	12	0.4	6.5	12	0.4
560	5.5	12	0.4	5.5	12	0.4	6.5	17	0.4
680	5.5	12	0.4	6.0	12	0.4	6.5	17	0.4

VDC	50VDC/100VDC			160VDC			500VDC/630VDC		
	PF	D	L	Ø d	D	L	Ø d	D	L
820	6.0	12	0.4	6.5	12	0.4	6.5	17	0.4
1000	6.0	12	0.4	6.5	17	0.4	7.0	17	0.4
1200	6.0	12	0.4	6.5	17	0.4	7.5	17	0.4
1500	6.5	12	0.4	6.5	17	0.4	7.5	21	0.4
1800	6.5	12	0.4	7.0	17	0.4	8.0	21	0.4
2200	6.5	12	0.4	7.0	17	0.5	8.0	22	0.4
2700	7.0	12	0.4	7.0	17	0.5	8.5	22	0.4
3300	7.0	12	0.4	7.5	19	0.5	9.0	24	0.5
3900	7.5	12	0.4	7.5	19	0.5	9.5	24	0.5
4700	8.0	12	0.4	8.0	19	0.5	10	24	0.5
5600	8.5	12	0.4	9.0	19	0.5	11	24	0.5
6800	9.0	12	0.4	9.5	19	0.5	11	24	0.5
8200	9.5	12	0.4	9.5	22	0.5	12	24	0.5
10000	10.0	12	0.4	10.5	22	0.5	13	24	0.5

Note: Specification are subject to change without notice. For more detail and update, please visit our website.