


PD1M 1mm InGaAs Photodiode


FEATURES

- Planar Structure
- Dielectric Passivation
- High Shunt Resistance
- High Responsivity

APPLICATIONS

- Sensing
- High Sensitivity Instrumentation







PD1M-1xx TO46 can Package

PRODUCT DESCRIPTION

The PD1M is an InGaAs photodiode with a photosensitive region 1mm in diameter. Applications include sensing and other high sensitivity instrumentation. Class A devices feature very low dark current and high shunt resistance.

High reliability is assured through planar semiconductor design and dielectric passivation. The device can be assembled on a ceramic submount or in an hermetic TO46 can. Custom packages are an option.

ELECTRICAL CHARACTERISTICS

Table 1: Electrical Specifications

PARAMETER	MIN	TYP	MAX	UNIT
Dark Current (I _D) (1)	-	50	-	nA
Capacitance (2)	-	150	-	pF
Responsivity at 1310nm	0.80	0.90	-	A/W
Responsivity at 1550nm	0.85	0.95	-	A/W
Rise/Fall time	-	15	-	ns
Shunt Resistance (Class A) (2)	50	-	-	ΜΩ
Shunt Resistance (Class B) (2)	1	-	-	ΜΩ

^{(1) 1}V reverse bias

^{(2) 0}V reverse bias

PD₁M



ELECTRICAL CHARACTERISTICS (cont)

Table 2: Absolute Maximum Ratings

rabio 117 tboolato maximam ratingo					
PARAMETER	MIN	MAX	UNIT		
Forward Current	-	100	mA		
Reverse Current	-	20	mA		
Reverse Voltage	-	2	V		
Operating Case Temperature	-40	+85	°C		
Storage Temperature	-40	+85	°C		
Soldering temperature (10 seconds)	-	+250	°C		

Stresses in excess of the absolute ratings may cause permanent damage. Functional operation is not implied under these conditions. Exposure to absolute ratings for extended periods of time may adversely affect reliability.

ORDERING INFORMATION

Part Number	Options		
PD1M-0xx	Custom defined size and electrical layout		
PD1M-1xx	Package: TO46		
	Number of pins: 2 or 3		
	Cap: Window, AR / Non-AR coated.		
	Cap plating: Gold or nickel		

Please contact Anadigics for the specific part number and pinout that suits your needs

ANADIGICS, Inc.

829 Flynn Road Camarillo, California 93012, U.S.A. Tel: +1 (805) 445-4500 Fax: +1 (805) 445-4502

URL: http://www.anadigics.com E-mail: Mktg@anadigics.com

IMPORTANT NOTICE

ANADIGICS, Inc. reserves the right to make changes to its products or discontinue any product at any time without notice. The product specifications contained in Advanced Product Information sheets and Preliminary Data sheets are subject to change prior to a product's formal introduction. Information in Data Sheets have been carefully checked and are assumed to be reliable; however, ANADIGICS assumes no responsibility for inaccuracies. ANADIGICS strongly urges customers to verify that the information they are using is current before placing orders.

WARNING

ANADIGICS products are not intended for use in life support appliances, devices, or systems. Use of an ANADIGICS product in any such application without written consent is prohibited.

Rev 1.0 2