
2SJ293

Silicon P-Channel MOS FET

HITACHI

November 1996


Application

High speed power switching

Features

- Low on-resistance
- High speed switching
- Low drive current
- 4 V gate drive device can be driven from 5 V source
- Suitable for switching regulator, DC-DC converter
- Avalanche ratings

Outline



2SJ293

Absolute Maximum Ratings (Ta = 25°C)

Item	Symbol	Ratings	Unit
Drain to source voltage	V_{DS}	−60	V
Gate to source voltage	V_{GS}	±20	V
Drain current	I_D	−15	A
Drain peak current	$I_{D(pulse)}^{*1}$	−60	A
Body to drain diode reverse drain current	I_{DR}	−15	A
Avalanche current	I_{AP}^{*3}	−15	A
Avalanche energy	E_{AR}^{*3}	19	mJ
Channel dissipation	P_{ch}^{*2}	30	W
Channel temperature	Tch	150	°C
Storage temperature	Tstg	−55 to +150	°C

Notes 1. $PW \geq 10 \mu s$, duty cycle $\geq 1\%$
2. Value at $T_c = 25^\circ C$
3. Value at $T_{ch} = 25^\circ C$, $R_g \geq 50 \Omega$

Electrical Characteristics ($T_a = 25^\circ\text{C}$)

Item	Symbol	Min	Typ	Max	Unit	Test conditions
Drain to source breakdown voltage	$V_{(BR)DSS}$	-60	—	—	V	$I_D = -10\text{ mA}$, $V_{GS} = 0$
Gate to source breakdown voltage	$V_{(BR)GSS}$	± 20	—	—	V	$I_G = \pm 100\text{ }\mu\text{A}$, $V_{DS} = 0$
Gate to source leak current	I_{GSS}	—	—	± 10	μA	$V_{GS} = \pm 16\text{ V}$, $V_{DS} = 0$
Zero gate voltage drain current	I_{DSS}	—	—	-250	μA	$V_{DS} = -50\text{ V}$, $V_{GS} = 0$
Gate to source cutoff voltage	$V_{GS(off)}$	-1.0	—	-2.25	V	$I_D = -1\text{ mA}$, $V_{DS} = -10\text{ V}$
Static drain to source on state resistance	$R_{DS(on)}$	—	0.075	0.095	Ω	$I_D = -8\text{ A}$, $V_{GS} = -10\text{ V}^{*1}$
		—	0.09	0.12	Ω	$I_D = -8\text{ A}$, $V_{GS} = -4\text{ V}^{*1}$
Forward transfer admittance	$ y_{fs} $	8	12	—	S	$I_D = -8\text{ A}$, $V_{DS} = -10\text{ V}^{*1}$
Input capacitance	C_{iss}	—	1450	—	pF	$V_{DS} = -10\text{ V}$, $V_{GS} = 0$,
Output capacitance	C_{oss}	—	670	—	pF	$f = 1\text{ MHz}$
Reverse transfer capacitance	C_{rss}	—	240	—	pF	
Turn-on delay time	$t_{d(on)}$	—	20	—	ns	$I_D = -8\text{ A}$, $V_{GS} = -10\text{ V}$,
Rise time	t_r	—	95	—	ns	$R_L = 3.75\text{ }\Omega$
Turn-off delay time	$t_{d(off)}$	—	230	—	ns	
Fall time	t_f	—	160	—	ns	
Body to drain diode forward voltage	V_{DF}	—	-1.5	—	V	$I_F = -15\text{ A}$, $V_{GS} = 0$
Body to drain diode reverse recovery time	t_{rr}	—	160	—	ns	$I_F = -15\text{ A}$, $V_{GS} = 0$, $di_F/dt = 50\text{ A}/\mu\text{s}$

Note 1. Pulse test

See characteristic curves of 2SJ290

